

WARRIOR LEVER BALL VALVES

Description

Warrior Lever Ball Valves are WRAS approved and supplied in sizes ranging from 15 - 28mm with either Blue or Red handles. BSPT valves are supplied with parallel female threads to ISO 28 (formerly BS 2779), while Compression ended valves are manufactured to BS EN 1254-2. All products in this range are compliant with EN331 / CE Marked and are rated to PN25.



Warrior Ball Valves provide a reliable and straightforward way to isolate flow quickly within a Plumbing and Heating system. They are engineered to have a smooth action and create a good seal with pipework.

Technical Data

Size range: 15mm to 28mm diameter
Pressure: 16 bar maximum
Approvals: ISO 28, EN1254-2 , EN331 (CE Marked).
Materials: Brass

Codes

BSPT LEVER BALL VALVES		
	Blue Handle	Red Handle
15mm	28460003	28460036
20mm	28460014	28460047
25mm	28460025	28460058

COMPRESSION LEVER BALL VALVES		
	Blue Handle	Red Handle
15mm	28460069	28460110
22mm	28460080	28460121
28mm	28460091	28460132

Other Information

Warrior Lever Ball Valves are designed to be fitted using standard tools. They are quick to use and straightforward to install plus offer the ability to easily isolate flow.

A full range of Warrior Plumbing Fittings and Consumables are available from your local BSS branch. These include Compression Fittings, End Feed Fittings, Solder Ring Fittings, Yellow Metal Brassware, TRV's TMV's and AAV's. All are high quality fittings and are WRAS approved. Warrior Lever Ball Valves are available in pack quantities only.