

WARRIOR THERMOSTATIC MIXING VALVE

Description

Warrior Thermostatic Mixing Valves (TMV's) are supplied conforming to the TMV 2 and the TMV 3 schemes and are WRAS approved. Two models are available, either 15mm or 22mm and Warrior TMV's also benefit from Anti-Scald technology. The robust and reliable Warrior TMV is also Building Regulations part G compliant and has been designed and manufactured to meet the general requirements of the NHS.



Compression fittings as standard mean Warrior TMV's are easy to install using standard tools (set of spanners) also the one piece cartridge construction improves reliability and keeps maintenance to a minimum.

Technical Data

Size range: 15mm and 22mm diameter
Pressure: 0.2 - 5 bar.
Temperature Range: 30 - 50 degrees
Temperature Stability: +/-2 degrees
Approvals: TMV 2, TMV 3
Materials: Brass

Codes

THERMOSTATIC MIXING VALVES	
	TRV + L/S
15mm	28460176
22mm	28460187

Other Information

Warrior TMV's are designed to reliably blend hot water with cold water to ensure a constant and safe water temperature. TMV's can be used on all devices with hot and cold feeds however are more often found on baths, showers, basins, etc.

A full range of Warrior Plumbing Fittings and Consumables are available from your local BSS branch. These include Compression Fittings, End Feed Fittings, Solder Ring Fittings, Yellow Metal Brassware

TRV's, AAV's and a wide range of Lever Ball Valves. All are high quality fittings and are WRAS approved.