

PRODUCT DATA SHEET

WARRIOR COMPRESSION FITTINGS

Description

Warrior Compression fittings are manufactured to BS EN1254-2 and are WRAS approved. Supplied in sizes from 15mm diameter to 28mm diameter and available in the form of Couplers, Elbows, Tees, Stop Ends, Reducing Sets, etc. Compression fittings are manufactured from high quality brass and are supplied with body of fitting nut and olive.



Compression fittings are designed to mechanically create a joint between the fitting and the pipe. When tightening the nut, you are compressing the olive onto the tube, creating a permanent seal.

Technical Data

Size range: 15mm to 28mm diameter

Pressure: 30 degrees = 16 bar, 65 degrees = 10 bar, 120 degrees = 5 bar

Approvals: BS EN1254-2 and WRAS

Materials: Brass

Codes

	Coupler	Elbow	Tee	Stop End
15mm	28430007	28430136	28430254	28430328
22mm	28430018	28430147	28430265	28430339
28mm	28430029	28430158	28430276	28430350

	Male Coupler	Female Coupler	Male Elbow	Female Elbow
15mm x 1/2"	28430040	28430095	28430169	28430210
15mm x 3/4"	28430051			
22mm x 3/4"	28430062	28430103	28430180	28430221
22mm x 1"	28430073	28430114		
28mm x 1"	28430084	28430125	28430191	28430232

22 x 15 x 15mm Reducing Tee	28430287	
15mm x 1/2" Wall Plate Elbow	28430243	

Created on: 30th Jun 2019

Version: 1

Last updated: 30th Jun 2019

Other Information

Warrior Compression Fittings are designed to be fitted using standard tools (set spanners). They are quick to use and straightforward to install plus offer the ability if necessary to demount and reconnect joints. (Maintaining use of the fitting body and replacement Nut and Olive).

A full range of Warrior Plumbing Fittings and Consumables are available from your local BSS branch. These include End Feed Fittings, Solder Ring Fittings, Yellow Metal Brassware, TRV's TMV's AAV's and a large range of Lever Ball Valves. All are high quality fittings and are WRAS approved. Warrior Compression is available in pack quantities only.

Created on: 30th Jun 2019

Version: 1

Last updated: 30th Jun 2019