

WARRIOR Malleable Fittings

Description

The Warrior Malleable Fittings Range is kite marked and made in accordance with BS EN 10242. The range is manufactured from Blackheart Malleable Iron and is banded. The threads for both male and female ends are BSP Taper.



Technical Data

Applications:

- Hot and Cold Water Services
- Gas installations
- Steam installations
- Central Heating systems
- Sprinkler systems

Material Specification

- Blackheart malleable conforming to BS EN 1562 designation EN-GJMB-300-6, ASTM A197 and ISO 5922 or equivalent.

Connections:

- Conform to the gauging requirements of BS EN 10226-2 and BS 21
- Screwed BSP Taper (BSPT) for both male and female threads

Designation Of Tee Sizes

- BS EN 10242 Method B (Run as first and second size, branch as the third.)

Product Features:

- Manufactured to BS EN 10242:1995 (BS 143 or 1256:2000 where not covered under BS EN 10242:1995)
- British Standard Kitemark approved
- Meets the safety requirements of the Pressure Equipment Directive 97/23/EC
- Threads conform to BS EN 10226-2 & BS 21
- Size range 1/2" to 2" (15mm to 50mm)
- Maximum Pressure Rating 25 Bar
- Temperature Range -20 Degrees Celsius to 120 Degrees Celsius

Other Information

A full range of Warrior Plumbing Fittings and Consumables are available from your local BSS branch. These include Compression Fittings, End Feed Fittings, Solder Ring Fittings, Yellow Metal Brassware, TRV's TMV's and AAV's. Warrior Lever Ball Valves are also available in pack quantities only.