



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)

Creation Date : 15.04.20
Revision Date : 08.07.22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BOSS CUTTING, THREADING & TAPPING FLUID
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

1.3. Details of the supplier of the safety data sheet

BSS Industrial
Boss Court
7 Barton Close
Grove Park
Leicester
LE19 1SJ
+44 (0)116 242 7800
enquiries@bssgroup.com

1.4. Emergency telephone number

Emergency Telephone Number - +44 (0)116 245 5500 (8:30am - 5:00pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1
Extremely flammable aerosol.

Pressurised container: May burst if heated.

Classification is based on test data.

Health: Not classified

Classification based on calculation method.

Environment: Not classified

Classification based on calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictogram(s):





Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)

Creation Date : 15.04.20
Revision Date : 08.07.22

Signal word: Danger

Hazard statement(s): H222 : Extremely flammable aerosol.

H229 : Pressurized container: May burst if heated.

Precautionary statement(s): P102 : Keep out of reach of children.

P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 : Do not spray on an open flame or other ignition source.

P251 : Do not pierce or burn, even after use.

P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501-2 : Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard

information: Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Highly refined low mineral oils/hydrocarbons	-	-	-	30-80	Asp. Tox. 1	H304	
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	01-2119485926-20	68512-91-4	270-990-9	20-40	Press. Gas, Flam. Gas 1	H280,H220	K,G
Explanation notes							
G : exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006							
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)							

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water If eye irritation persists: Get medical advice/attention.



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID **Creation Date :** 15.04.20
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN) **Revision Date :** 08.07.22
Contact with skin : Take off contaminated clothing and wash before reuse.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Ingestion : If swallowed accidentally, do not induce vomiting and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion : May cause gastrointestinal disturbances
Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact : May cause irritation.
Symptoms : redness and pain
Eye contact : May cause irritation.
Symptoms : redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible If symptoms persist always call a doctor)

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID

Creation Date : 15.04.20

Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)

Revision Date : 08.07.22

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material
Place in appropriate container

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep in a cool, dry, well ventilated place
Keep out of reach of children.

7.3. Specific end use(s)

Lubricants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

No information available



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)

Creation Date : 15.04.20
Revision Date : 08.07.22

8.2. Exposure controls

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection : Take precautions to avoid contact with skin and eyes when handling the product.

Ensure adequate ventilation

Inhalation : In case of insufficient ventilation, wear suitable respiratory equipment. **hands and skin :** When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.

Recommended gloves: Nitrile

eyes : Wear safety eyewear according to EN 166.

Environmental protection: Avoid release to the environment.

Collect spillage.

Consumer exposure

Protection: Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Appearance : physical state : Propane/butane propelled liquid.

colour : Yellow.

odour : Characteristic odor.

pH : Not applicable.

Boiling point/range : Not available.

Flash point : 192 °C

Evaporation rate : Not available.

Explosion limits : upper limit : Not available.

lower limit : Not available.

Vapour pressure : Not available.

Relative density : 0.870 g/cm³ (@ 20°C).

Solubility in water : Immiscible with water

Auto-ignition : Not available.

Viscosity : 26 cSt @ 40°C

9.2. Other information

VOC = volatile organic

compounds 190 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)
No hazardous reactions known if used for its intended purpose

Creation Date : 15.04.20
Revision Date : 08.07.22

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met **skin corrosion/irritation:** based on available data the classification criteria are not met **serious eye damage/irritation:** based on available data the classification criteria are not met **respiratory or skin**

sensitisation: based on available data the classification criteria are not met **germ cell mutagenicity:** based on available data the classification criteria are not met **carcinogenicity:** based on available data the classification criteria are not met **toxicity for reproduction:** based on available data the classification criteria are not met **STOT-single exposure:** based on available data the classification criteria are not met **STOT repeated exposure:** based on available data the classification criteria are not met **aspiration hazard:** based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Ingestion : May cause gastrointestinal disturbances

Skin contact : Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis

Repeated exposure may cause skin dryness or cracking.

Eye contact : May cause irritation.

Toxicological data :



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)
No information available

Creation Date : 15.04.20
Revision Date : 08.07.22

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

No information available

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

Immiscible with water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available

GWP (global warming potential): 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)

Creation Date : 15.04.20
Revision Date : 08.07.22

14.2. UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1
ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally
hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally
hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)
IMDG - Ems: F-D, S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO 203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Regulation (EC) No 1907/2006 (REACH)
Regulation (EC) No 1272/2008 (CLP)
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS CUTTING, THREADING & TAPPING FLUID
Version: 1.1 **Ref.Nr.:** UDS000967_3_20200415 (EN)

Creation Date : 15.04.20
Revision Date : 08.07.22

SECTION 16: Other information

*Explanation hazard statements: H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.

acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistent bioaccumulative toxic
vPvB = very persistent very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission.