

COROLFIX

VERTICAL PLASTIC SPACERS



Updated on 23/08/2024

Presentation

- COROLFIX are spacers for vertical reinforcement, ensuring that rebars are held securely in place.
- They are available in a range of colors on request, depending on the model.
- Consumption: 4 to 6 COROLFIX per m².

Composition & manufacturing

- Spacers made of High Density Polyethylene (HDPE), low pressure grade 5 to 7.
- Manufacturing method : Plastic injection.

Usage

Code	Désignation	Φ of rebar (mm)	Concrete cover (mm)
006170	COROLFIX 5-12/15	5 à 12	15
006171	COROLFIX 5-12/20	5 à 12	20
006172	COROLFIX 5-12/25	5 à 12	25
012748	COROLFIX 5-12/30	5 à 12	30
006174	COROLFIX 5-12/35	5 à 12	35
006175	COROLFIX 5-14/40	5 à 14	40
006176	COROLFIX 5-14/50	5 à 14	50

Packaging

Code	Désignation	Sales Multiple	Weight per 100 (kg)
006170	COROLFIX 5-12/15	1000 p.	0.30
006171	COROLFIX 5-12/20	500 p.	0.34
006172	COROLFIX 5-12/25	1250 p.	0.63
012748	COROLFIX 5-12/30	1250 p.	0.76
006174	COROLFIX 5-12/35	1000 p.	1.26
006175	COROLFIX 5-14/40	1000 p.	1.60
006176	COROLFIX 5-14/50	500 p.	2.60

The information provided in this document is for guidance only and reflects our current knowledge. We shall not be responsible or liable for any improper or inappropriate use of our products.

Given the wide range of possible uses, our recommendations do not exempt users from carrying out their own tests. Our laboratory and technical department will be happy to provide you with any information you may require.

TAM Groupe Z.I. Avenue Albert Einstein.
CS 90043 - 77555 Moissy Cramayel Cedex - France
S.A.S. au capital de 883 332 € RCS Melun B
SIRET 313 659 674 00029 - FR 76 313 659 674

Tel.: + 33 1 64 13 30 00 – tamgroupe@tamgroupe.fr – www.tamgroupe.fr