

MANDFIX

PLASTIC SPACERS



Updated on 10/08/2023

Characteristics

Ideal for pre-casting elements in washed, sanded or sandblasted concrete, or for rough concrete.

Can be used for both horizontal and vertical shimming.

For small diameter rebars, fix MANDFIX at rebar intersection.

Various colors on request

Dimensions et packaging

Article No	Designation	Ø rebar in mm	Cover in mm	Packaging	Weight per 100
00092	MANDFIX 20	4 à 18	20	2000 p.	0.65
000093	MANDFIX 25	4 à 18	25	1250 p.	0.68
000096	MANDFIX 30 REINFORCED	4 à 18	30	1000 p.	0.86
000097	MANDFIX 35 REINFORCED	4 à 18	35	1000 p.	0.88
000098	MANDFIX 40 REINFORCED	4 à 18	40	1000 p.	0.94

The information provided in this document is for guidance only and reflects our current knowledge. We shall not be responsible or liable for any improper or inappropriate use of our products.

Given the wide range of possible uses, our recommendations do not exempt users from carrying out their own tests. Our laboratory and technical department will be happy to provide you with any information you may require.

TAM Groupe Z.I. Avenue Albert Einstein.
CS 90043 - 77555 Moissy Cramayel Cedex - France
S.A.S. au capital de 883 332 € RCS Melun B
SIRET 313 659 674 00029 - FR 76 313 659 674

Tel. : + 33 1 64 13 30 00 – tamgroupe@tamgroupe.fr – www.tamgroupe.fr