

UNICALE II

PLASTIC SPACERS



Updated 23/07/2024

Characteristics

UNICALE II are U shaped linear plastic spacers. They have the following advantages:

- Quick, easy and labour saving installation.
- Wide cut-outs facilitate the flow of concrete while preserving stability and reducing the visibility on the finished concrete surface.
- Can be used in horizontal, vertical or inclined position.
- Very resistant and adequate for all diameters.
- Can easily be cut into spacers of 33 or 50 cm for point support.
- Spacer made of PVC (CFC & HFC free).

Application

- The spacers are to be laid diagonally to the reinforcement to ensure the required concrete cover.
- *NOTE : Protect the spacers against direct sunlight during storage*



Dimensions & packaging

Code	Product name	Height (mm)	Sale multiple (ml)	Standard packaging (ml)	Weight of 100 ml (kg)
016637	UNICALE II / PP H20 -2.00ML	20	100	6300	15,1
001677	UNICALE II / PP H25 -2.00ML	25	100	4900	18
001678	UNICALE II / PP H30 - 2.00ML	30	100	4200	20
001687	UNICALE II / PP H40 - 2.00ML	40	60	2400	25
001694	UNICALE II / PP H50 - 2.00ML	50	60	1680	39
017505	UNICALE II / PP H60 - 2.00ML	60	40	1280	49

The information provided in this document is for guidance only and reflects our current knowledge. We shall not be responsible or liable for any improper or inappropriate use of our products.

Given the wide range of possible uses, our recommendations do not exempt users from carrying out their own tests. Our laboratory and technical department will be happy to provide you with any information you may require.

TAM Groupe Z.I. Avenue Albert Einstein.
CS 90043 - 77555 Moissy Cramayel Cedex - France
S.A.S. au capital de 883 332 € RCS Melun B
SIRET 313 659 674 00029 - FR 76 313 659 674

Tel. : + 33 1 64 13 30 00 – tamgroupe@tamgroupe.fr – www.tamgroupe.fr