

ANCHOR FOOT

ANCHORAGES



Updated on 27/06/2023

Characteristics

- Anchor foot to be used with the corresponding TOURBILLON® tie bar.
- Admissible tension load is function of the depth of anchorage, concrete strength, axial distance for anchorages and concrete edge distance.
- Anchor foot is weldable (Steel : S255).
- Non-perforated version available on request.

Steel working loads et dimensions

Diameter		Ø17	Ø23	Ø30
Designation		20.60S	30.80S	40.115S
Reference		100239	100283	100313
Height H	mm	52	62	67
Dimension A	mm	60	78	115
Weight	g	230	505	1460
Packaging		50	25	15
With PVC tube		22x26	32x38	40x46
Working load	kN	95	172	290
Failure load	kN	195	345	580

The information provided in this document is for guidance only and reflects our current knowledge. We shall not be responsible or liable for any improper or inappropriate use of our products.

Given the wide range of possible uses, our recommendations do not exempt users from carrying out their own tests. Our laboratory and technical department will be happy to provide you with any information you may require.

TAM Groupe Z.I. Avenue Albert Einstein.
CS 90043 - 77555 Moissy Cramayel Cedex - France
S.A.S. au capital de 883 332 € RCS Melun B
SIRET 313 659 674 00029 - FR 76 313 659 674

Tel.: + 33 1 64 13 30 00 – tamgroupe@tamgroupe.fr – www.tamgroupe.fr