

SupaCool R134a



Description

Supa Cool R134a is non-flammable and toxicologically safe.

R134a was introduced as the first refrigerant substitute to replace R12 in practically all applications.

Applications

- Household refrigerators
- Automobile air conditioners
- Heat pumps
- Centrifugal water chillers for air conditioning in buildings, for transport and commercial refrigeration

Hazard statement(s)

- Contains gas under pressure; may explode if heated.

Prevention statement(s)

- None allocated.

Response statement(s)

- None allocated.

Storage statement(s)

- Protect from sunlight. Store in a well-ventilated place.

Other hazards

- Asphyxiant. Effects are proportional to oxygen displacement.

Signal Word: Warning
UN No.: 3159
Hazard No.: 2TE
Chem Symbol: N/A
Pictograms:



SupaCool R134a



General Specifications

Specifications	12.5 Cyl.	22 Cyl.	65 Cyl.
Cylinder/Pack (101.325kPa @15°C) - kg	11.0	22.0	65.0
Water capacity per cylinder - L	11.0	22.0	65.0
Cylinder Colour	Light Blue		
Outlet Connection	Type 34		
Package Dimensions (H x W x D) - mm	260 x 404	310 x 505	377 x 859

Cylinder dimensions are approximate – variations may occur due to manufacturing tolerances. Height includes the valve.

Package Sizes Available



Quality Assurance

Supagas Pty Ltd is committed to comply with the requirements of ISO 9001-2015 and to continually improve the effectiveness of our Quality Management System.

Everyone at Supagas understands we must provide a safe environment for both our employees and the wider community. We are therefore committed to implement and maintain a continual improvement approach throughout the organisation whilst also meeting all applicable statutory and regulatory requirements.

For Further Information

On how we can help you with all your gas and welding needs, drop in to your local Supagas branch or call Customer Service on 13 78 72.

Typical Analysis

Chemical Name	Molecular Formula	Composition
1,1,1,2-Tetrafluoroethane	$C_2H_2F_4$	100%