





BACK-UP ALARMS




800 SERIES

Surface Mount

Designed to meet all the harsh operational requirements of any fleets equipment, ECCO's 800 Series alarms feature a reverse-mounted speaker design and reinforced nylon housing providing unrivaled durability. These alarms are so robust that an ECCOLIFE™ warranty covering the alarm for the life of the vehicle is offered on all models. These 800 Series alarm models feature a mounting bracket with the same mounting pattern popular with OEM's. Smart Alarm® models measure ambient noise and adjust their sound level, creating a volume that is safe without being annoying or contributing to noise pollution. Smart Alarms eliminate the need for constant manual adjustment and help prevent intentional alarm disconnection. Ask your local representative for any supporting documents and certifications.

Models				
PART NO.	TYPE	VOLTS	DECIBELS	AMPS
SA907N	Smart	12-24	82-107	1.12
SA917N	Smart	12-24	87-112	1.5
SA914N	OEM Mounting	12-24	87-112	1.5
840N	-	12-36	97/112 Switchable	1.4
830N	-	12-36	107	1.1
850N	-	12-36	112	1.3
876N	OEM Mounting	12-36	112	1.3



Alarm Specifications

Connection: 16 AWG blunt cut wires Reinforced nylon housing Recommended mounting bolt:

Bottom: 3/8-16 UNC Grade 5 or better

Recommended washer:

Bottom: 3/8" Type A Series N washer Recommended mounting torque:

Bottom: 50 in. lbs.

Design Features

- Mounting backet features popular OEM footprint
- Reverse-mounted speaker enhances sound and protects the speaker from dust and moisture ingress
- Reinforced nylon housing eliminates corrosion damage
- · Sealed in epoxy for protection against dust, moisture and vibration
- Temperature Range: -40°F to +185°F (-40°C to +85°C)