



## BEACONS





















excludes  
7265C, CG,  
CAG & 7260

## EB7260 SERIES

### Mini Pole Mount

ECCO's EB7260 Series LED Beacon produces a warning signal that is ideal for industrial applications. The long, maintenance-free service life of LED technology makes this a perfect replacement solution for existing strobe beacons. This cost-effective, SAE Class II light features 12-24V operating range that also makes it ideal for use on electrically powered vehicles and equipment.



### Models

PART NO.	FLASH PATTERNS	LENS COLOR	LED COLOR OPTIONS
EB7265A	41	 A	 A
EB7265C	41	 C	 C
EB7265CX	41	 C	 A  B  G  R
EB7265CXX	96	 C	 A  B  G  R
EB7260A	41	 A	 C
EB7260CA	41	 C	 A

Replace "X" in part number with desired color: A=amber, B=blue, C=clear, G=green, R=red

### Design Features

- 12-24 VDC, 1.4 Amps, 75 -120 FPM
- 3 Bolt or 1/2" Pipe-Mount
- Economical-style beacon with several flash pattern options
- Removable flange assembly for easy pipe-mount configuration
- Flash Mode - Single: 75 - 120, Double: 75
- Reinforced polycarbonate flange and lens
- Temperature Range: -22°F to +122°F (-30°C to +50°C)



Base Diameter = 4.67 [119]

