





SAFETY DIRECTOR™



ED3300 SERIES

High-Intensity Warning

The ED3300 LED Safety Director™ is a high-intensity warning system designed to direct traffic approaching from the rear of a stationary vehicle. The light-stick design allows for unobtrusive interior or exterior mounting, either flush to the vehicle or using the provided mounting brackets. Inside the cab a modern, soft touch controller provides fingertip control of the ED3300's nine built-in flash patterns, features an LED display that mimics the selected pattern in real time and also includes an auxiliary switch. 20A auxiliary relay included.

M	0	d	e	S

CABLE LENGTH	ILLUMINATION
15' 4.6m	=
35' 9.1m	=
55' 16.8m	=
	15' 4.6m 35' 9.1m

Features and Benefits


- 12-24 VDC, 1.5 Amps
- Extruded aluminum housing with polycarbonate lens
- Eight reflective modules with 20 LEDs
- Includes signal bar, controller, cable and 20A auxiliary relay
- Temperature Range: -22°F to +122°F (-30°C to +50°C)

System Components

•	Controller:	341	0CB
•	Signal bar:	ED3	300LBA
•	Cable:	15′	(3410-15)
		35′	(3410-35)
		55'	(3410-55)

Replacement Parts

Amber Module:	ER3300A
Blue Module:	ER3300B
Clear Module:	ER3300C
Red Module:	ER3300R



Flash Patterns

LEFT (L)	LEFT SOLID (LS)
CENTER OUT (C)	CENTER OUT SOLID (CS)
RIGHT/R)	RIGHT SOLID (RS)
RIGHT(R)	RIGHT SOLID (RS)
RIGHTIR	RIGHT SOLID (RS)
RIGHTIR	RIGHT SOLID (RS)
RIGHT(R)	RIGHT SOLID (RS)
	ALTERNATING QUAD FLASH (AQF)