



CAMERA SYSTEMS






K7000B 7" LCD Color System

The 7" LCD high-resolution color monitor included with this system provides the optimal viewing area for mobile CCTV applications. Excellent picture quality is assured even in low-light conditions using a CMOS color infrared camera. The flat, widescreen monitor allows unobtrusive mounting with a large, easily viewable screen area. Expandable up to 2 cameras.




Design Features

- CMOS 18 LED infrared camera
- Integrated molded shroud
- Two camera expandable
- Monitor with touch & backlight buttons
- 1292 x 968 HD camera resolution

Components

-  M7000B
-  C2013B
-  ECTC20-4 (20m/65')

Expansion Options

-  Any current ECCO camera
-  ECTC5-4 (5m/16'), ECTC10-4 (10m/32'),
-  ECTC20-4 (20m/65')

M7000B



internal controller	Yes
color	Yes
voltage	12-24
power consumption (W)	5.0
day / night light sensor	Yes
dimensions	6.85" x 4.49" x 0.94"
weight	0.88 lbs
temperature (F°)	-4 to +158
screen size	7.0"
mirror image	Yes
sunshade	Yes
max cameras	2
4 pin camera connection	Yes

C2013B



color	Yes
power consumption (W)	1.0
day / night light sensor	Yes
dimensions	2.92" x 3.01" x 2.62"
weight	0.6 lbs
temperature (F°)	-22 to +158
lens angle	75° Horizontal 170° Vertical
lens size	1/3"
infrared LEDs	18
mechanical vibration	8G
4 pin camera connection	Yes (threaded connection)

WIRING GUIDE

