



CAMERA SYSTEMS



camera only

monitor only




K7000B Gemineye™ 7" LCD Color System

The 7" LCD high-resolution color monitor included with this system provides the optimal viewing area for mobile CCTV applications. Excellent picture quality is assured even in low-light conditions using a CMOS color infrared camera. The flat, widescreen monitor allows unobtrusive mounting with a large, easily viewable screen area. Expandable up to 2 cameras.



FEATURES & BENEFITS

- CMOS 18 LED infrared camera
- Integrated molded shroud
- Two camera expandable
- Monitor with touch & backlight buttons
- 768 x 592V camera resolution

COMPONENTS

-  M7000B
-  C2013B
-  ECTC20-4 (20m/65')

EXPANSION OPTIONS

-  Any current ECCO camera
-  ECTC5-4 (5m/16'), ECTC10-4 (10m/32'), ECTC20-4 (20m/65')



M7000B

| | |
|--------------------------|-----------------------|
| internal controller | Yes |
| color | Yes |
| voltage | 12-24 |
| power consumption (W) | 5.0 |
| day / night light sensor | Yes |
| dimensions | 6.85" x 4.49" x 0.94" |
| weight | 0.88 lbs |
| temperature (F°) | -4 to +158 |
| screen size | 7.0" |
| mirror image | Yes |
| sunshade | Yes |
| max cameras | 2 |
| 4 pin camera connection | Yes |



C2013B

| | |
|--------------------------|---------------------------------|
| color | Yes |
| power consumption (W) | 1.0 |
| day / night light sensor | Yes |
| dimensions | 2.92" x 3.01" x 2.62" |
| weight | 0.6 lbs |
| temperature (F°) | -22 to +158 |
| lens angle | 75° Horizontal 170° Vertical |
| lens size | 1/3" |
| infrared LEDs | 18 |
| mechanical vibration | 8G |
| 4 pin camera connection | Yes (threaded connection) |

WIRING GUIDE

