

NING LIGHTING | DIRECTIONA

ING SAFE



# CAMERA Sysi

II R 10 RoHS RCM (IP69K)







#### Camera Only

# EC7003-K Gemineye<sup>TM</sup> 7" LCD Color System

The 7" LCD high-resolution touchscreen color monitor included with this system provides the optimal viewing area for mobile CCTV applications. Excellent picture quality is assured even in low-light conditions using ECCO's CMOS color infrared camera. The flat, widescreen monitor allows unobtrusive mounting with a large, easily viewable screen area. Expandable up to 3 cameras.


#### **FEATURES & BENEFITS**

- Touchscreen menu control
- CMOS 11 LED infrared camera
- Includes monitor sunshade
- Three camera expandable

## **COMPONENTS**



EC2014-C



### **EXPANSION OPTIONS**

Any current ECCO camera

ECTC5-4 (5m/16'), ECTC10-4 (10m/32'), ECTC20-4 (20m/65')

**ACCESSORIES & REPLACEMENT PARTS** 

PC1.8Y-4 Wire Harness



	EC7003-M
approvals	FCC, CE, R10, RoHS RCM
internal controller	Yes
color	Yes
voltage	12-24
power consumption (W)	6
audio	Yes
day / night light sensor	Yes
dimensions	8.4" x 6" x 2.8"
weight	3.3 lbs
temperature	-4 to +158
screen size	7.0"
mirror image	Yes
remote control	Yes
sunshade	Yes
max cameras	3
4 pin camera connection	Yes



	EC2014-C
approvals	FCC, CE, R10, RoHS, RCM, IP69K
color	Yes
power consumption (W)	3
microphone	Yes
day / night light sensor	Yes
dimensions	2.87" x 2.99" x 2.60"
weight	0.74 lbs
temperature	-22 to +158
lens angle	120°
lens size	1/3"
infrared LEDs	11
mechanical vibration	10G
4 pin camera connection	Yes (threaded connection)

