star plus, neo and primo Reversible single cylinders

Key Figures

Lifetime per unit: 15 years Weight per unit: 0.45 kg Production location: Yokohama, Japan

Production standards

| Quality | Environmental | Occupational Health & Safety | Energy | Produced with green electricity |
|---------|---------------|---------------------------------|--------|---------------------------------|
| | | | | |

Product declarations

| Environmental Product Declaration | Health Product Declaration | Building Product Declaration | SuPIM Data Sheet |
|--------------------------------------|----------------------------|------------------------------|------------------|
| ✓ | | | |

Material used (%)

■ Brass ■ Steel ■ Nickel silver ■ Plastic



The GWP¹ across the life cycle is 1.55 kg CO_2e

This is similar to the CO₂ produced from a road trip with a diesel mid-range car from Rümlang to Zürich airport



¹ Carbon dioxide equivalent (CO₂e) is the universal unit of measurement to indicate the global warming potential (GWP) of each of the six greenhouse gases, expressed in terms of the GWP of one unit of carbon dioxide. It is used to evaluate releasing (or avoiding releasing) different greenhouse gases against a common basis.



Scan the QR code or click here for more information about sustainability



Scan the QR code or click here for more information about our sustainability product declaration.

Description

star plus, neo and primo are mechanical key systems. They offer legal protection against commercial imitation. The registration of individual locking systems, and master key systems with dormakaba ensure that keys cannot be ordered without authorization. The systems can be used in both the private sector as well as for large and complex buildings with high security requirements. star plus, neo and primo can be equipped with RFID transponder for integration in electronic access systems from dormakaba.

Total Global Warming Potential per life cycle stage (kg CO_2e)



