

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	dormakaba International Holding GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DOR-20260198-CBA1-EN
Issue date	16.03.2026
Valid to	15.03.2031

Overhead Door Closer TS Match Series dormakaba

www.ibu-epd.com | <https://epd-online.com>



General Information

dormakaba

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-DOR-20260198-CBA1-EN

This declaration is based on the product category rules:

Building Hardware products, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

16.03.2026

Valid to

15.03.2031



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

Overhead Door Closer TS Match Series

Owner of the declaration

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

Declared product / declared unit

1 piece of the product: Overhead Door Closer TS Match Series consisting of the following items:

- Door closer body
- Cover
- Slide channel
- Arm
- Mounting plate
- Product packaging

Scope:

This Environment Product Declaration refers to a specific Overhead Door Closer TS Match Series manufactured by dormakaba. The production site is located in Singapore.


The data represents the year 2024.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Matthias Klingler,
(Independent verifier)

Product

Product description/Product definition

The TS Match and TS Match X are part of the dormakaba slide channel door closer range. Both models offer adjustable closing speed and are compatible with an optional concealed mounting plate. These features make them suitable for integration into door systems as part of initial equipment specifications.

For the Overhead Door Closer TS Match Series the standards which can be applied are the following:

- EN 1154

The *CE marking* takes into account the proof of conformity with the respective harmonized standards based on the legal provisions above.

Application

The Overhead Door Closer TS Match Series is designed for commercial and institutional applications and is suitable for internal and external doors. It can be used in a variety of applications, including as door closer for fire, anti-flame and smoke check doors (non-hold-open versions).

Technical Data

The Overhead Door Closer TS Match Series has following technical properties:

Data and features		
	Size EN 3-5	Size EN 3-4
Closing force adjustable Standard doors	≤ 1250 mm •	≤ 1100 mm •
External doors, outward opening ≤ 1250 mm	≤ 1250 mm •	≤ 1100 mm •
Fire and smoke control doors ≤ 1250 mm	≤ 1250 mm •	≤ 1100 mm •
Same design for DIN-L and DIN-R	•	•
Arm assembly type Slide channel	•	•
Adjustable closing speed via a valve 180°- 0°	•	•
Adjustable latching speed via a valve 7° 0°	•	•
Adjustable backcheck via a valve	•	•

LCA: Calculation rules

Declared Unit

The declared unit is 1 piece of the product: Overhead Door Closer TS Match Series including packaging

Name	Value	Unit
Declared unit	1	piece/product
Mass of declared Product	2.03	kg
Mass of Packaging	0.25	kg
Total Mass of declared product	2.28	kg

System boundary

The type of EPD is: cradle to gate with options, modules C1–C4, and module D (A1–A3 + C + D and additional modules: A4+ A5)

Production - Module A1-A3

•yes – no ○ option

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision which can be applied are mentioned above.

Base materials/Ancillary materials

The major material composition including the packaging of the product is listed below:

Name	Value	Unit
Aluminium	42	%
Steel	39	%
Packaging	11	%
Lubricants	6	%
Plastics	1	%
Zinc	1	%

The products include partial articles which contain substances listed in the Candidate List of REACH Regulation 1907/2006/EC (date: 25.01.2025) exceeding 0.1 percentage by mass: yes

- Lead (Pb): 7439-92-1 (CAS-No.) is included in some of the alloys used. The concentration of lead in each individual alloy does not exceed 0.38% (by mass).

The *Candidate List* can be found on the ECHA website address: <https://echa.europa.eu/de/home>.

Manufacture

The system consists of a door closer body and compatible slide rails, primarily made of metal components with supplementary plastic parts and hydraulic oil. The TS Match Series is manufactured and assembled in dormakaba production facilities in Singapore. The specific manufacturing steps and processes may vary depending on the product type and configuration.

Reference service life

The reference service life of the Overhead Door Closer TS Match Series is about 20 years, depending on the application and frequency of use. For repairs and renewals, suitable spare parts are available. The door closer is tested and certified to EN 1154, meaning they are designed to withstand a minimum of 500,000 cycles.

The product stage includes: — A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes), — A2, transport to the manufacturer, — A3, manufacturing and assembly including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state. The electricity used corresponds to an average emission factor of 0.49 kg CO₂ equivalent per kWh.

Construction stage - Modules A4-A5

The construction process stage includes: — A4, transport to the building site; — A5, installation into the building; including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction process stage.

End-of-life stage– Modules C1-C4 and D

The end-of-life stage includes: — C1, de-construction, demolition; — C2, transport to waste processing; — C3, waste processing for reuse, recovery and/or recycling; — C4, disposal; including provision and all transport, provision of all materials, products and related energy and water use. Module D (Benefits and loads beyond the system boundary) includes: — D, recycling potentials, expressed as net impacts and benefits.

Geographic Representativeness

Land or region, in which the declared product system is

manufactured, used or handled at the end of the product’s lifespan: Singapore

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Background database: GaBi, CUP 2024.2.

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	0.09	kg C

Singapore is considered for A3.

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.00276	l/100km
Capacity utilisation (including empty runs) average	55	%
Transport distance for scaling (truck)	100	km
Transport distance via truck (from dormakaba to harbor)	500	km
Transport distance (ship)	13000	km

The product is transported via truck and ship. The product is stored in the dormakaba logistic center in Wuppertal. The main distribution regions are Asia and Europe with the calculated transport distances. In order to allow scalling to a specific point of installation 100 km are declared as well.

Installation into the building (A5)

Name	Value	Unit
Waste packaging (paper)	0.25	kg

Reference service life

Name	Value	Unit
Life Span according to the manufacturer	20	a

End of life (C1-C4)

C1: The product dismantling from the building is done manually without environmental burden.

C2: Transport to waste treatment at end of life is 50km.

C4: There are no mineral substances that require landfilling; therefore, no expenses are incurred in module C4.

Name	Value	Unit
Collected separately waste type	2.03	kg
Recycling	1.85	kg
Energy recovery	0.18	kg

The product is disassembled in a recycling process. Material recycling is then assumed for metals. The plastic components are assumed to be incinerated with energy recovery. The minor proportions of residues arising from the recycling process are landfilled. Region for the End of Life is: Global.

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Recycling	100	%

The collection rate is 100 %.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 piece Overhead Door Closer TS Match Series

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	2.4E+01	2.51E-01	3.99E-01	0	1.05E-02	4.58E-01	0	-7.64E+00
GWP-fossil	kg CO ₂ eq	2.44E+01	2.45E-01	8.16E-03	0	1.01E-02	4.58E-01	0	-7.62E+00
GWP-biogenic	kg CO ₂ eq	-3.62E-01	5.98E-03	3.9E-01	0	4.37E-04	-2.48E-06	0	-1.51E-02
GWP-luluc	kg CO ₂ eq	7.42E-03	8.91E-06	5.42E-06	0	3.93E-07	2.95E-05	0	-1.47E-03
ODP	kg CFC11 eq	8.61E-11	2.02E-14	4.78E-14	0	8.76E-16	1.66E-13	0	-4.61E-11
AP	mol H ⁺ eq	9.87E-02	3.67E-03	9.75E-05	0	1.11E-05	7.74E-05	0	-2.63E-02
EP-freshwater	kg P eq	1.28E-05	6.38E-08	1.36E-08	0	2.56E-09	3.87E-08	0	-3.55E-06
EP-marine	kg N eq	1.94E-02	9.17E-04	3.59E-05	0	3.96E-06	1.71E-05	0	-3.74E-03
EP-terrestrial	mol N eq	2.12E-01	1.01E-02	4.46E-04	0	4.49E-05	3.59E-04	0	-4.03E-02
POCP	kg NMVOC eq	5.86E-02	2.62E-03	9.51E-05	0	1.16E-05	4.77E-05	0	-1.21E-02
ADPE	kg Sb eq	7.54E-05	5.91E-09	5.05E-10	0	2.61E-10	1.5E-09	0	-2.51E-05
ADPF	MJ	2.54E+02	3.18E+00	1.08E-01	0	1.4E-01	2.28E-01	0	-1.01E+02
WDP	m ³ world eq deprived	2.93E+00	4.71E-04	4.34E-02	0	2.02E-05	4.29E-02	0	-3.23E-01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 piece Overhead Door Closer TS Match Series

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	4.67E+01	1.55E-02	3E+00	0	6.75E-04	8.19E-02	0	-4.05E+01
PERM	MJ	2.97E+00	0	-2.97E+00	0	0	0	0	0
PERT	MJ	4.96E+01	1.55E-02	2.94E-02	0	6.75E-04	8.19E-02	0	-4.05E+01
PENRE	MJ	2.53E+02	3.18E+00	1.08E-01	0	1.4E-01	1.13E+00	0	-1.01E+02
PENRM	MJ	9.04E-01	0	0	0	0	-9.04E-01	0	0
PENRT	MJ	2.54E+02	3.18E+00	1.08E-01	0	1.4E-01	2.28E-01	0	-1.01E+02
SM	kg	6.49E-01	0	0	0	0	0	0	1.28E+00
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
FW	m ³	7.77E-02	1.9E-05	1.02E-03	0	8.23E-07	1.03E-03	0	-1.21E-01

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 piece Overhead Door Closer TS Match Series

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	7.76E-07	9.85E-11	6.14E-11	0	4.32E-12	1.85E-10	0	-7.15E-08
NHWD	kg	4.01E+00	3.05E-04	1.1E-02	0	1.34E-05	4.58E-02	0	-1.55E+00
RWD	kg	2.46E-03	3.59E-06	5.43E-06	0	1.56E-07	7.16E-06	0	-9.79E-03
CRU	kg	0	0	0	0	0	0	0	0
MFR	kg	6.99E-01	0	0	0	0	1.85E+00	0	0
MER	kg	0	0	0	0	0	0	0	0
EEE	MJ	0	0	5.3E-01	0	0	7E-01	0	0
EET	MJ	0	0	9.61E-01	0	0	1.62E+00	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:
1 piece Overhead Door Closer TS Match Series**

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	1.63E-06	6.46E-08	5.36E-10	0	1.01E-10	8.92E-10	0	-4.14E-07
IR	kBq U235 eq	2.98E-01	4.92E-04	8.54E-04	0	2.13E-05	7.62E-04	0	-1.98E+00
ETP-fw	CTUe	2E+02	2.35E+00	4.71E-02	0	1.04E-01	8.71E-02	0	-2.16E+01
HTP-c	CTUh	5.75E-03	4.26E-11	2.8E-12	0	1.88E-12	7.08E-12	0	-6.32E-08
HTP-nc	CTUh	1.36E-07	1.34E-09	5.53E-11	0	5.89E-11	5.35E-10	0	-3.17E-08
SQP	SQP	5.85E+01	1.11E-02	3.29E-02	0	4.83E-04	7.48E-02	0	-2.34E+00

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

This EPD was created using a software tool.

References

EN 1154

DIN EN 1154: 2003---04: Building hardware – Controlled door closing devices Requirements and test methods (includes amendment A1:2002); German version / EN 1154:1996 +A1:2002

EN 15804

EN 15804+A2:2019+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

ECHA

European Chemical Agency

ISO 14025

DIN EN ISO 14025:201110, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

REACH

Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Further References

IBU 2021

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. Version 2.1, Berlin: Institut Bauen und Umwelt e.V., 2022. www.ibu-epd.com

SPHERA LCA FE

Sphera LCA for Experts, LCA FE, Software system and databases, Managed LCA content MLC (fka GaBi database), University of Stuttgart and Sphera Solutions GmbH

MLC documentation

MLC life cycle inventory data documentation
<https://lcadatabase.sphera.com/>

LCA-tool dormakaba

Tool No.: IBU-DOR-202508-LT2-EN
Developed by Sphera Solutions GmbH

PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report according to EN15804+A2:2019, Version 1.4, 2024, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

PCR Part B

PCR – Part B: Requirements on the EPD for Building Hardware product, version 08/2021, Institut Bauen und Umwelt e.V., www.ibu-epd.com.



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

+49 711 341817-0
info@sphera.com
www.sphera.com



Owner of the Declaration

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

+49 2333 793-0
info.de@dormakaba.com
www.dormakaba.com