

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	Skyfold Inc.
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-SKY-20260462-CBA1-EN
Issue date	26.08.2026
Valid to	25.08.2031

Movable Wall Zenith/Zenith® Premium Series Skyfold

www.ibu-epd.com | <https://epd-online.com>



General Information

Skyfold

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-SKY-20260462-CBA1-EN

This declaration is based on the product category rules:

Room partition systems, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

26.08.2026

Valid to

25.08.2031



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Dr. Martina Bender
(Managing Director Institut Bauen und Umwelt e.V.)

Movable Wall Zenith/Zenith® Premium Series

Owner of the declaration

Skyfold Inc.
Avenue Lee 325
H9X 3S3 Montréal
Canada

Declared product / declared unit

1 m² of the Movable Wall Zenith/Zenith® Premium Series consisting of the following items:

- Panel assembly
- Lifting mechanism assembly
- Motor assembly
- Product packaging

Scope:

This Environmental Product Declaration refers to a movable wall manufactured by Skyfold. The declared unit corresponds to 1 m² of product. Each panel represents an area of 30 ft². The production site is located in Baie D'Urfé, Québec (Canada).

The EPD is representative for the Skyfold's Movable Wall Zenith/Zenith® Premium Vinyl, Movable Wall Zenith/Zenith® Premium Fabric and Movable Wall Zenith/Zenith® Premium Laminate. The declared results are based on the Movable Wall Zenith/Zenith® Premium Vinyl, which represents the worst-case scenario.


Electricity consumption is based on the Canadian national grid mix which has a high share of renewable energy sources (primarily hydropower).

The data represents the year 2025.
The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidence.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard is abbreviated as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
☐	internal
☒	external



Matthias Klingler,
(Independent verifier)

Product

Product description/Product definition

The Zenith/Zenith® Premium Series is an automated operable movable wall system with vertical, straight-down deployment. It is designed for interior space division in areas with limited floor space and is available in multiple acoustic performance levels (STC/Rw). The Zenith® Premium Series includes enhanced ceiling integration while maintaining the same deployment mechanism and acoustic functionality.

For the use and application of the product the respective national provisions at the place of use apply:

- *Sound Transmission Class (STC)*
- *Americans with Disabilities Act (ADA)*

Application

Skyfold Zenith/Zenith® Premium Series are intended for interior applications including commercial office environments to fit in rooms with tall ceilings, such as conference rooms, auditoriums, hotel ballrooms, gymnasiums as well as convention centers.

Technical data

Technical specifications of the products included in the LCA scope, as well as product performance testing results are available on the manufacturer's website (www.skyfold.com).

Name	Value	Unit
Airborne sound reduction	48 / 51 / 55 / 60	dB

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision which can be applied are mentioned above.

This EPD follows the additional requirements for construction products considered as electronic or electric equipment.

Base materials/auxiliary materials

LCA: Calculation rules

Declared unit

The declared unit is 1 m² of the product: Skyfold Zenith/Zenith® Premium Series including packaging

Name	Value	Unit
Declared unit	1	m ²
Grammage	70.85	kg/m ²
Weight (per ft ²)	6.58	kg
Weight (per ft ²)	14.51	lb
Weight (per m ²)	156.2	lb
Layer thickness	0.02	m

1 m² = 10.7639 ft²

1 kg/m² = 0.205 lb/ft²

1 Inch = 0.0254 m

System boundary

The type of EPD is: cradle to gate with options, modules C1–C4, and module D (A1-A3 + C + D and additional modules: A4+A5+B6)

The major material composition including the packaging of the product is listed below:

Name	Value	Unit
Steel	67	%
Wood	15	%
Plastics	8	%
Aluminium	7	%
Paper	2	%
Others	1	%

The product includes partial articles which contain substances listed in the Candidate List of REACH Regulation 1907/2006/EC (date: 04.02.2026) exceeding 0.1 percentage by mass: no

The *Candidate List* can be found on the ECHA website address: <https://echa.europa.eu/de/home>.

Manufacture

Skyfold Zenith® operable wall systems are custom-manufactured by Skyfold Inc. in an ISO 9001-certified facility in Baie D'Urfé, Québec, Canada. The manufacturing process generally consists of controlled, factory-based assembly operations, including fabrication of steel-faced acoustic panels, assembly of aluminum and steel structural frames, integration of acoustic cores, seals, and mechanical lifting systems, as well as installation of electrical and control components. Finishes are applied according to project specifications, followed by quality inspection and functional testing. Completed wall assemblies are then packaged for shipment to site. Specific manufacturing steps and materials may vary depending on wall size, acoustic rating, and selected finishes.

Reference service life

The reference service life of Skyfold Zenith/Zenith® Premium Series movable wall is about 50 years, depending on the application and frequency of use (approx. 50 closing cycles per year). For repairs and renewals, suitable spare parts are available.

Production - Module A1-A3

The product stage includes: — A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes), — A2, transport to the manufacturer, — A3, manufacturing and assembly including provision of all materials, products and the Canadian national grid mix, which has a high share of renewable energy sources (primarily hydropower), as well as waste processing up to the end-of-waste state. The electricity used corresponds to an average emission factor of 0.170 kg CO₂ equivalent per kWh.

Construction stage - Modules A4-A5

The construction process stage includes: — A4, transport to the building site; — A5, installation into the building; including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction process stage.

Use stage - Module B6

The use stage related to the operation of the building includes:

— B6, operational energy use.

End-of-life stage - Modules C1-C4 and D

The end-of-life stage includes: — C1, de-construction, demolition; — C2, transport to waste processing; — C3, waste processing for reuse, recovery and/or recycling; — C4, disposal; including provision and all transport, provision of all materials, products and related energy and water use. Module D (Benefits and loads beyond the system boundary) includes: — D, recycling potentials, expressed as net impacts and benefits.

Geographic representativeness

Country or region in which the declared product system is manufactured, used or handled at the end of the product's life span: North America

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all data sets to be compared were created according to *EN 15804* and the building context and product-specific performance characteristics are taken into account.

Background database: GaBi, CUP 2024.2.

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Name	Value	Unit
Biogenic carbon content in product	0	kg C / lb C
Biogenic carbon content in accompanying packaging	5.34 / 11.77	kg C / lb C

Baie D'Urfé, Québec (Canada) is considered for A3.

Note: 1 kg (2.20 lb) of biogenic carbon is equivalent to 44/12 kg of CO₂.

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.0276	l/tkm
Transport distance	100	km
Transport distance	62.1	mi
Capacity utilisation (including empty runs)	55	%

The product is transported via truck. The main distribution region is US. In order to allow scaling to a specific point of installation 100 km / 62.1 mi are declared.

Installation into the building (A5)

Name	Value	Unit
Waste packaging (paper)	1.70 / 0.35	kg per m ² / lb per ft ²
Waste packaging (wood)	10.25 / 2.10	kg per m ² / lb per ft ²

Reference service life

Name	Value	Unit
Reference service life	50	a

Operational energy use (B6)

373 W reflects the power used per m² of product area. The value is derived from the energy use of one door operator and a product area of 30 ft².

Name	Value	Unit
Days per year in use	26	days
Electricity consumption for 1 year (per m ² of a unit)	0.23	kWh
Electricity consumption for 1 year (per ft ² of a unit)	0.02	kWh
On mode power (per unit)	373	W
On mode per day (per unit)	0.02	hr
Off mode per day (per unit)	23.98	hr

End of life (C1-C4)

C1: The product dismantling from the building is done manually without environmental burden.

C2: Transport to waste management is 50 km.

Name	Value	Unit
Collected separately waste type	58.9 / 129.85	kg / lb
Recycling	51.1 / 112.65	kg / lb
Energy recovery	5.8 / 12.78	kg / lb
Landfilling	1.98 / 4.36	kg / lb

The product is disassembled in a recycling process. Material recycling is then assumed for the metals, and electronics. The plastic components, glass wool are assumed to be incinerated with energy recovery. Electromechanics are assumed to be landfilled. Region for the End of Life is: Global

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Recycling	100	%

The collection rate is 100 %.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	X	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m² Movable Wall Zenith/Zenith® Premium Series

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	1.54E+02	7.31E-01	1.97E+01	5.44E+00	0	3.04E-01	1.46E+01	2.99E-02	-8.86E+01
GWP-fossil	kg CO ₂ eq	1.65E+02	7.01E-01	3.84E-01	5.43E+00	0	2.91E-01	1.46E+01	2.96E-02	-8.87E+01
GWP-biogenic	kg CO ₂ eq	-1.17E+01	3.04E-02	1.94E+01	2.32E-03	0	1.26E-02	-7.91E-05	9.41E-05	1.26E-01
GWP-luluc	kg CO ₂ eq	8.09E-02	2.74E-05	1.09E-04	1.05E-03	0	1.14E-05	9.4E-04	1.78E-04	-1.21E-02
ODP	kg CFC11 eq	5.97E-10	6.11E-14	2.22E-12	3.53E-11	0	2.54E-14	5.31E-12	7.99E-14	-2.95E-10
AP	mol H ⁺ eq	5.29E-01	7.72E-04	8.94E-03	1.11E-02	0	3.21E-04	2.47E-03	2.1E-04	-2.41E-01
EP-freshwater	kg P eq	2.96E-04	1.79E-07	5.42E-07	3.94E-06	0	7.42E-08	1.23E-06	6.73E-08	-4.6E-05
EP-marine	kg N eq	1.17E-01	2.76E-04	4.18E-03	2.15E-03	0	1.15E-04	5.45E-04	5.41E-05	-3.71E-02
EP-terrestrial	mol N eq	1.34E+00	3.13E-03	4.86E-02	2.33E-02	0	1.3E-03	1.15E-02	5.96E-04	-3.68E-01
POCP	kg NMVOC eq	3.73E-01	8.08E-04	1.08E-02	6.31E-03	0	3.36E-04	1.52E-03	1.66E-04	-1.32E-01
ADPE	kg Sb eq	2.43E-03	1.82E-08	2.41E-08	5.48E-07	0	7.55E-09	4.8E-08	1.92E-09	-2.92E-04
ADPF	MJ	2.04E+03	9.77E+00	5.7E+00	8.98E+01	0	4.06E+00	7.27E+00	3.91E-01	-1.12E+03
WDP	m ³ world eq deprived	3.01E+01	1.41E-03	2.04E+00	1.25E+00	0	5.85E-04	1.37E+00	3.39E-03	-5.83E+00

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m² Movable Wall Zenith/Zenith® Premium Series

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
PERE	MJ	8.27E+02	4.7E-02	1.55E+02	2.61E+01	0	1.95E-02	2.62E+00	6.82E-02	-2.64E+02
PERM	MJ	1.54E+02	0	-1.54E+02	0	0	0	0	0	0
PERT	MJ	9.8E+02	4.7E-02	1.37E+00	2.61E+01	0	1.95E-02	2.62E+00	6.82E-02	-2.64E+02
PENRE	MJ	1.93E+03	9.77E+00	5.7E+00	8.98E+01	0	4.06E+00	1.14E+02	3.91E-01	-1.12E+03
PENRM	MJ	1.07E+02	0	0	0	0	0	-1.07E+02	0	0
PENRT	MJ	2.04E+03	9.77E+00	5.7E+00	8.98E+01	0	4.06E+00	7.27E+00	3.91E-01	-1.12E+03
SM	kg	2.21E+01	0	0	0	0	0	0	0	3.17E+01
RSF	MJ	0	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0	0
FW	m ³	1.12E+00	5.73E-05	4.8E-02	3.82E-02	0	2.38E-05	3.28E-02	1.04E-04	-5.1E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 m² Movable Wall Zenith/Zenith® Premium Series

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
HWD	kg	7.59E-06	3.01E-10	2.88E-09	5.16E-08	0	1.25E-10	5.92E-09	9.73E-11	-3.79E-06
NHWD	kg	2.24E+01	9.35E-04	2.03E-01	3.28E-02	0	3.88E-04	1.46E+00	1.98E+00	-2.72E+00
RWD	kg	7.6E-02	1.09E-05	2.58E-04	8.94E-03	0	4.52E-06	2.29E-04	4.1E-06	-6.52E-02
CRU	kg	0	0	0	0	0	0	0	0	0
MFR	kg	6E-03	0	0	0	0	0	5.11E+01	0	0
MER	kg	0	0	0	0	0	0	0	0	0
EEE	MJ	1.42E+01	0	2.28E+01	0	0	0	2.24E+01	0	0
EET	MJ	2.56E+01	0	4.07E+01	0	0	0	5.18E+01	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 m² Movable Wall Zenith/Zenith® Premium Series

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
PM	Disease incidence	8.45E-06	7.07E-09	2.84E-08	1.33E-07	0	2.94E-09	2.85E-08	2.64E-09	-3.03E-06
IR	kBq U235 eq	9.61E+00	1.49E-03	4.08E-02	7.86E-01	0	6.18E-04	2.43E-02	4.75E-04	-1.16E+01
ETP-fw	CTUe	7.11E+02	7.24E+00	1.98E+00	2.14E+01	0	3.01E+00	2.78E+00	2.25E-01	-1.55E+02
HTP-c	CTUh	7.24E-07	1.31E-10	1.41E-10	8.21E-10	0	5.44E-11	2.26E-10	5.31E-12	7.98E-09
HTP-nc	CTUh	1.14E-06	4.11E-09	2.34E-09	1.59E-08	0	1.71E-09	1.71E-08	2.05E-10	-1.42E-07
SQP	SQP	1.4E+03	3.37E-02	1.49E+00	1.04E+01	0	1.4E-02	2.39E+00	1.08E-01	-6.16E+01

PM = Potential incidence of disease due to PM emissions; IR = Potential human exposure efficiency relative to U235; ETP-fw = Potential comparative toxic unit for ecosystems; HTP-c = Potential comparative toxic unit for humans (carcinogenic); HTP-nc = Potential comparative toxic unit for humans (not carcinogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – carcinogenic”, “Potential comparative toxic unit for humans - not carcinogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

This EPD was created using a software tool.

References

ADA

Americans with Disabilities Act 1990

<https://www.ada.gov/>

STC

Sound Transmission Class

<https://asastandards.org/terms/sound-transmission-class/>

ISO 9001

DIN EN ISO 9001:2025-09, Quality management systems - Requirements (ISO/DIS 9001:2025); German and English version prEN ISO 9001:2025

ISO 14001

DIN EN ISO 14001:2015-11, Environmental management systems - Requirements with guidance for use (ISO 14001:2015); German and English version EN ISO 14001:2015

NRC

Noise Reduction Coefficient

<https://asastandards.org/terms/noise-reduction-coefficient/>

EN 15804

EN 15804:2012+A1 2013, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

EN 15804

EN 15804:2012+A2:2019+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

ISO 14025

EN ISO 14025:2011, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

Further References

IBU 2022

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. Version 2.1, Berlin: Institut Bauen und Umwelt e.V., 2022. www.ibu-epd.com.

SPHERA LCA FE

Sphera LCA for Experts, LCA FE, Software system and databases, Managed LCA content MLC (fka GaBi database), University of Stuttgart and Sphera Solutions GmbH

MLC documentation

MLC life cycle inventory data documentation

<https://lcadatabase.sphera.com/>

LCA-tool dormakaba

Tool No.: IBU-DOR-202508-LT2-EN.

Developed by Sphera Solutions GmbH

PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report according to EN15804+A2:2019, Version 1.4, 2024, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

PCR Part B

PCR – Part B: Requirements on the EPD for Room partition systems, version 08/2021, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

The literature referred to in the Environmental Product Declaration must be listed in full. Standards already fully quoted in the EPD do not need to be listed here again. The current version of PCR Part A and PCR Part B of the PCR document on which they are based must be referenced.



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the life cycle assessment

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

+49 2333 793-0
info.de@dormakaba.com
www.dormakaba.com



Owner of the Declaration

Skyfold Inc.
Avenue Lee 325
H9X 3S3 Montréal
Canada

+1 (514) 457-4767
info@skyfold.com
www.skyfold.com