

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2




Owner of the Declaration	dormakaba International Holding GmbH
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DOR-20210304-CBA1-EN
Issue date	04.05.2022
Valid to	03.05.2027

BEST 1C Series dormakaba

www.ibu-epd.com | <https://epd-online.com>



General Information

dormakaba Programme holder IBU – Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany	BEST 1C Series Owner of the declaration dormakaba International Holding GmbH DORMA Platz 1 58256 Ennepetal Germany
Declaration number EPD-DOR-20210304-CBA1-EN	Declared product / declared unit 1 core (1 piece) of the BEST 1C Series.
This declaration is based on the product category rules: Building Hardware products, 11.2017 (PCR checked and approved by the SVR)	Scope: This Environmental Product Declaration refers to a specific core manufactured by dormakaba. The production site is located in Indianapolis (USA).
Issue date 04.05.2022	The data represents the year 2020.
Valid to 03.05.2027	The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences. The EPD was created according to the specifications of <i>EN 15804+A2</i> . In the following, the standard will be simplified as <i>EN 15804</i> .
 Dipl. Ing. Hans Peters (chairman of Institut Bauen und Umwelt e.V.)	Verification The standard <i>EN 15804</i> serves as the core PCR Independent verification of the declaration and data according to <i>ISO 14025:2010</i> <input type="checkbox"/> internally <input checked="" type="checkbox"/> externally
 Dr. Alexander Röder (Managing Director Institut Bauen und Umwelt e.V.)	 Dr.-Ing. Wolfram Trinius (Independent verifier)

Product

Product description/Product definition

BEST Cores draw on the legacy of quality and expertise that keep our products on the forefront of the industry. Brass alloy construction result in reliable performance over time. BEST Cores allow for easier rekeying by allow a user to remove the core from the lock without the need to remove the lever.

For the use and application of the product the respective national provisions at the place of use apply. The standards which can be applied are the following:

- *ANSI/BHMA 156.5*
- *BAA/TAA*
- *UL listed*

Application

BEST Cores are designed for commercial and institutional applications, where seamless removal of the core from its hardware is needed.

Technical Data

The cores have following technical properties:

General	
BHMA Standard	BEST - SFIC
Product Specifications	AI565, Grade I
Utility Patent	2027
Physical:	
Core Material	Brass
Key Material	Nickel-Silver
8 Finishes	605, 606, 611, 612, 613, 625, 626, 690
Core Size (pin count)	6 or 7
Keyway Count (excluding multi-milling) *	> 30
Key System	A2, A4
Security Levels: **	
(W) Non-exclusive	Available
(X) Two-digit zip code exclusive	Available
(Y) One-digit zip code exclusive	Available
(Z) National exclusive	Available
Features:	
Warranty	3 year limited
Pick & Drill Resistant	Option
Key Trap	Option
Wear Resistant	Option
M series keys are backward compatible with standard J,K,L,M keyways	M,J,M,K,M,L,M,M
Milling (sectional keyways) Capability	Double, Quad
Construction Core to Permanent Keying Support	Yes
Keystone - Key and Core Control Management***	Service Option
BESTCode - Masterkey System Support	Service Option
Custom Key Stamping ***	Service Option

technical provision which can be applied are mentioned above.

Base materials/Ancillary materials

Name	Value	Unit
Brass	93	%
Steel	3	%
Paper	2	%
Others	>1	%

The product/s include/s partial articles which contain substances listed in the Candidate List of *REACH* Regulation 1907/2006/EC (date: 17.01.2022) exceeding 0.1 percentage by mass: yes

- Lead (Pb): 7439-92-1 (CAS-No.) is included in some of the alloys used. The concentration of lead in each individual alloy does not exceed 4.0% (by mass).

The *Candidate List* can be found on the *ECHA* website address: <https://echa.europa.eu/de/home>.

Reference service life

The reference service life of the BEST 1C Series cores depend on the traffic pattern and degree of usage of the core. The BEST 1C Series is certified to *BHMA/ANSI Grade 1*, meaning they are designed to withstand a minimum of 40,000 uses.

Performance data of the product with respect to its characteristics in accordance with the relevant

LCA: Calculation rules

Declared Unit

The declared unit is 1 piece of the product: BEST 1C Series.

Declared unit

Name	Value	Unit
Declared unit	1	piece/product
Mass of declared Product	0.0449	kg

System boundary

The type of EPD is: cradle to gate with options, modules C1–C4, and module D (A1–A3 + C + D and additional modules: A4 + A5)

Production - Module A1-A3

The product stage includes:
 — A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes),
 — A2, transport to the manufacturer,
 — A3, manufacturing and assembly including provision of all materials, products and energy, as well as waste processing up to the end-of waste state.

Construction stage - Modules A4-A5

The construction process stage includes:

— A4, transport to the building site;
 — A5, installation into the building;
 including provision of all materials, products and energy, as well as waste processing up to the end-of waste state or disposal of final residues during the construction process stage.

End-of-life stage– Modules C1-C4 and D

The end-of-life stage includes:
 — C1, de-construction, demolition;
 — C2, transport to waste processing;
 — C3, waste processing for reuse, recovery and/or recycling;
 — C4, disposal;
 including provision and all transport, provision of all materials, products and related energy and water use. Module D (Benefits and loads beyond the system boundary) includes:
 — D, recycling potentials, expressed as net impacts and benefits.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

Background database: *GaBi*, SP40.

LCA: Scenarios and additional technical information

Characteristic product properties Information on biogenic Carbon

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic Carbon Content in accompanying packaging	0	kg C

Additional technical information for the declared modules.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel per 1 kg (truck)	0.00276	l/100km
Transport distance truck	1500	km
Capacity utilisation (including empty runs) average	55	%
Transport distance (ship)	10000	km

Installation into the building (A5)

Name	Value	Unit
Output substances following waste treatment on site (packaging)	0.0011	kg

End of life (C1-C4)

C1: The product dismantling from the building is done manually without environmental burden.
C2: Transport to waste treatment at end of life is 50km.

Name	Value	Unit
Collected separately	0.0438	kg
Recycling	0.0438	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Collection rate is 100%.		

LCA: Results

Disclaimer:

EP-freshwater: This indicator has been calculated as “kg P eq” as required in the characterization model (EUTREND model, Struijs et al., 2009b, as implemented in ReCiPe; <http://eplca.jrc.ec.europa.eu/LCDN/developerEF.xhtml>)

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	MNR	MNR	MNR	X	ND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 core

Core Indicator	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
GWP-total	[kg CO ₂ -Eq.]	3.10E-1	7.00E-3	2.00E-3	0.00E+0	0.00E+0	1.92E-4	0.00E+0	0.00E+0	2.00E-3
GWP-fossil	[kg CO ₂ -Eq.]	3.00E-1	7.00E-3	3.91E-5	0.00E+0	0.00E+0	1.83E-4	0.00E+0	0.00E+0	2.00E-3
GWP-biogenic	[kg CO ₂ -Eq.]	9.05E-3	2.62E-4	2.00E-3	0.00E+0	0.00E+0	8.46E-6	0.00E+0	0.00E+0	-3.56E-6
GWP-luluc	[kg CO ₂ -Eq.]	1.59E-4	1.64E-7	2.57E-8	0.00E+0	0.00E+0	4.36E-9	0.00E+0	0.00E+0	3.03E-6
ODP	[kg CFC11-Eq.]	1.35E-14	7.33E-19	2.81E-19	0.00E+0	0.00E+0	1.93E-20	0.00E+0	0.00E+0	6.35E-18
AP	[mol H ⁺ -Eq.]	9.26E-4	5.97E-5	4.37E-7	0.00E+0	0.00E+0	1.83E-7	0.00E+0	0.00E+0	4.24E-5
EP-freshwater	[kg PO ₄ -Eq.]	2.52E-7	1.54E-9	5.50E-11	0.00E+0	0.00E+0	3.92E-11	0.00E+0	0.00E+0	8.54E-9
EP-marine	[kg N-Eq.]	1.28E-4	1.61E-5	1.58E-7	0.00E+0	0.00E+0	5.83E-8	0.00E+0	0.00E+0	2.41E-6
EP-terrestrial	[mol N-Eq.]	1.38E-3	1.76E-4	1.97E-6	0.00E+0	0.00E+0	6.48E-7	0.00E+0	0.00E+0	2.62E-5
POCP	[kg NMVOC-Eq.]	3.83E-4	4.50E-5	4.18E-7	0.00E+0	0.00E+0	1.65E-7	0.00E+0	0.00E+0	8.55E-6
ADPE	[kg Sb-Eq.]	2.04E-5	2.07E-10	4.44E-12	0.00E+0	0.00E+0	5.49E-12	0.00E+0	0.00E+0	4.43E-6
ADPF	[MJ]	4.74E+0	9.80E-2	4.92E-4	0.00E+0	0.00E+0	3.00E-3	0.00E+0	0.00E+0	2.40E-2
WDP	[m ³ world-Eq deprived]	6.90E-2	1.37E-5	1.93E-4	0.00E+0	0.00E+0	3.59E-7	0.00E+0	0.00E+0	1.00E-3

Caption: GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 core

Indicator	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
PERE	[MJ]	8.52E-1	3.10E-4	1.30E-2	0.00E+0	0.00E+0	8.19E-6	0.00E+0	0.00E+0	7.00E-3
PERM	[MJ]	1.30E-2	0.00E+0	-1.30E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	8.65E-1	3.10E-4	8.95E-5	0.00E+0	0.00E+0	8.19E-6	0.00E+0	0.00E+0	7.00E-3
PENRE	[MJ]	4.74E+0	9.80E-2	4.93E-4	0.00E+0	0.00E+0	3.00E-3	0.00E+0	0.00E+0	2.50E-2
PENRM	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PENRT	[MJ]	4.74E+0	9.80E-2	4.93E-4	0.00E+0	0.00E+0	3.00E-3	0.00E+0	0.00E+0	2.50E-2
SM	[kg]	4.50E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m ³]	2.44E-3	5.58E-7	4.55E-6	0.00E+0	0.00E+0	1.47E-8	0.00E+0	0.00E+0	6.98E-6

Caption: PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 core

Indicator	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
HWD	[kg]	4.06E-9	9.50E-12	7.26E-13	0.00E+0	0.00E+0	2.52E-13	0.00E+0	0.00E+0	2.80E-10
NHWD	[kg]	1.50E-2	9.99E-6	4.89E-5	0.00E+0	0.00E+0	2.66E-7	0.00E+0	0.00E+0	1.01E-4
RWD	[kg]	4.14E-4	1.06E-7	2.59E-8	0.00E+0	0.00E+0	2.79E-9	0.00E+0	0.00E+0	1.10E-6
CRU	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	4.40E-2	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	1.70E-2	0.00E+0	2.00E-3	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	[MJ]	3.10E-2	0.00E+0	4.00E-3	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0

Caption: HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:

1 core

Indicator	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
PM	[Disease Incidence]	7.66E-9	9.54E-10	2.42E-12	0.00E+0	0.00E+0	9.63E-13	0.00E+0	0.00E+0	3.09E-10
IRP	[kBq U235-Eq.]	3.80E-2	1.51E-5	4.01E-6	0.00E+0	0.00E+0	3.99E-7	0.00E+0	0.00E+0	-8.56E-5
ETP-fw	[CTUe]	1.78E+0	6.90E-2	2.34E-4	0.00E+0	0.00E+0	2.00E-3	0.00E+0	0.00E+0	4.10E-2
HTP-c	[CTUh]	1.90E-10	1.30E-12	1.24E-14	0.00E+0	0.00E+0	3.46E-14	0.00E+0	0.00E+0	7.09E-13
HTP-nc	[CTUh]	2.95E-9	5.68E-11	5.36E-13	0.00E+0	0.00E+0	1.48E-12	0.00E+0	0.00E+0	2.17E-10
SQP	[-]	9.00E-1	2.53E-4	1.31E-4	0.00E+0	0.00E+0	6.67E-6	0.00E+0	0.00E+0	2.30E-2
Caption	PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index									

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”.

This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”.

The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.

References

ANSI/BHMA A156.5

ANSI/BHMA A156.4 - 2014, Cylinders and Input Devices for Locks.

EN 15804:2019+A2

EN 15804:2019+A2 (in press), Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Further References

Buy American Act (BAA).

Trade Agreements Act (TAA).

IBU

Institut Bauen und Umwelt e.V.: General Instructions for the EPDs programme of Institut Bauen und Umwelt e.V. Version 2.0., Berlin: Institut Bauen und Umwelt e.V., 2021. www.ibu-epd.com.

GaBi ts software

Sphera Solutions GmbH
Gabi Software System and Database for Life Cycle Engineering 1992-2020
Version 10.0.0.71
University of Stuttgart
Leinfelden-Echterdingen

GaBi ts documentation

GaBi life cycle inventory data documentation (<https://www.gabi-software.com/support/gabi/gabidatabase-2020-lci-documentation/>).

LCA-tool dormakaba

LCA-tool, IBU-DOR-202104-LT1-EN.
Developed by Sphera Solutions GmbH

PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Re-port according to EN 15804+A2:2019, Version 1.0, 2020, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

PCR Part B

PCR – Part B: Requirements on the EPD for Building Hardware product, version 1.2, Institut Bauen und Umwelt e.V., www.ibu-epd.com, 2017.

Underwriters Laboratories (UL).

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

**Author of the Life Cycle
Assessment**

Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

Tel +49 711 341817-0
Fax +49 711 341817-25
Mail info@sphera.com
Web www.sphera.com

**Owner of the Declaration**

dormakaba International Holding
GmbH
DORMA Platz 1
58256 Ennepetal
Germany

Tel +49 2333 793-0
Fax +49 2333 793-4950
Mail info.de@dormakaba.com
Web www.dormakaba.com