


ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	Modernfold Inc.
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-MOF-20250610-CBA1-EN
Issue date	03.02.2026
Valid to	02.02.2031

Glass Wall System PureView Modernfold

www.ibu-epd.com | <https://epd-online.com>



General Information

Modernfold

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-MOF-20250610-CBA1-EN

This declaration is based on the product category rules:

Room partition systems, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

03.02.2026

Valid to

02.02.2031

Glass Wall System PureView

Owner of the declaration

Modernfold Inc.
West New Road 215
46140 Greenfield, IN
United States

Declared product / declared unit

1 m² of the Glass Wall System PureView consisting of the following items:

- Glass pane
- Product packaging

Scope:

This Environmental Product Declaration refers to the Glass Wall System Pureview manufactured by Modernfold. The declared unit corresponds to 1 m² of product. Each panel represents an area of 32 ft².The production site is located in Dyersville, IA (USA).

The data represents the year 2024.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR

Independent verification of the declaration and data according to ISO
14025:2011


internally externally



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)



Matthias Klingler,
(Independent verifier)

Product

Product description/Product definition

The PureView movable glass partition system offers a flexible and modern space management solution, designed to enhance daylighting and maintain uninterrupted sightlines. Engineered for performance and durability, PureView combines high-quality manufacturing standards with user-friendly operation. It is available in multiple configurations including Single Panel, Paired Panel and Continuously Hinged and offers acoustical control up to 37 STC. The system features a range of glass and finish options, double vinyl top and bottom seals, foot-operated interconnecting floor bolts for added security, and the flexibility to choose from over 170 RAL powder-coated colors. With its refined aesthetics and robust functionality, PureView® is ideal for creating adaptable, visually open environments without compromising on privacy or sound control.

For the use and application of the product the respective national provisions at the place of use apply:

- *Sound Transmission Class (STC)*
- *Americans with Disabilities Act (ADA)*

Application

PureView movable glass partition systems are intended for interior applications including commercial office environments, education, healthcare, hospitality, and multi-purpose spaces and provide the primary function of partitioning interior spaces.

Technical Data

Technical specifications of the products included in the LCA scope, as well as product performance testing results are available on the manufacturer's website (<https://www.modernfold.com/en-US/downloads/product-documents>).

Name	Value	Unit
Airborne sound reduction	15	dB

LCA: Calculation rules

Declared Unit

The declared unit is 1 m² of the product: Glass Wall System PureView including packaging

Name	Value	Unit
Declared unit	1	m ²
Grammage	18.79	kg/m ²
Weight (per ft ²)	1.75	kg
Weight (per ft ²)	3.85	lb
Weight (per m ²)	41.41	lb
Layer thickness	0.04	m

$$1 \text{ m}^2 = 10,7639 \text{ ft}^2$$

$$1 \text{ kg/m}^2 = 0.205 \text{ lb/ft}^2$$

$$1 \text{ Inch} = 0.0254 \text{ m}$$

System boundary

The type of EPD is: cradle to gate with options, modules C1–C4, and module D (A1–A3 + C + D and additional modules: A4+ A5)

Production - Module A1-A3

The product stage includes: — A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes), — A2,

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision which can be applied are mentioned above.

Base materials/Ancillary materials

The major material composition including the packaging of the product is listed below:

Name	Value	Unit
Glass	64	%
Aluminium	16	%
Steel	10	%
Packaging	7	%
Plastics	3	%

The product includes partial articles which contain substances listed in the Candidate List of REACH Regulation 1907/2006/EC (date: 05.11.2025) exceeding 0.1 percentage by mass: no

The *Candidate List* can be found on the ECHA website address: <https://echa.europa.eu/de/home>.

Manufacture

The manufacturing process primarily consists of short line and long line assembly operations. Key stages include frame layup, frame assembly, trimming, inspection, and final packaging. The specific manufacturing steps and processes may vary depending on the product type and configuration.

Reference service life

The reference service life of PureView is about 25 years, depending on the application and frequency of use (approx. 50 closing cycles per year). For repairs and renewals, suitable spare parts are available.

transport to the manufacturer, — A3, manufacturing and assembly including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state. The electricity used corresponds to an average emission factor of 0.46 kg CO₂ equivalent per kWh.

Construction stage - Modules A4-A5

The construction process stage includes: — A4, transport to the building site; — A5, installation into the building; including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction process stage.

End-of-life stage - Modules C1-C4 and D

The end-of-life stage includes: — C1, de-construction, demolition; — C2, transport to waste processing; — C3, waste processing for reuse, recovery and/or recycling; — C4, disposal; including provision and all transport, provision of all materials, products and related energy and water use. Module D (Benefits and loads beyond the system boundary) includes: — D, recycling potentials, expressed as net impacts and benefits.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: United States

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created

according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Background database: GaBi, CUP 2024.2.

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Name	Value	Unit
Biogenic carbon content in product	0	kg C / lb C
Biogenic carbon content in accompanying packaging	0.57 / 1.26	kg C / lb C

Dyersville, IA (USA) is considered for A3.

Note: 1 kg (2.20 lb) of biogenic carbon is equivalent to 44/12 kg of CO₂.

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.0276	l/tkm
Transport distance	100	km
Transport distance	62.1	mi
Capacity utilisation (including empty runs)	55	%

The product is transported via truck. The main distribution region is US. In order to allow scaling to a specific point of installation 100 km / 62.1 mi are declared.

Installation into the building (A5)

Name	Value	Unit
Waste packaging (wood)	1.23 / 0.25	kg per m ² / lb per ft ²

Reference service life

Name	Value	Unit
Reference service life	25	a

End of life (C1-C4)

C1: The product dismantling from the building is done manually without environmental burden.

C2: Transport to waste management is 50 km.

Name	Value	Unit
Collected separately waste type	17.6 / 38.8	kg / lb
Recycling	4.95 / 10.91	kg / lb
Energy recovery	0.62 / 1.37	kg / lb
Landfilling	12 / 26.46	kg / lb

The product is disassembled in a recycling process. Material recycling is then assumed for the metals. The plastic components are assumed to be incinerated with energy recovery. Glass is assumed to be landfilled. Region for the End of Life is: Global

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Recycling	100	%

The collection rate is 100 %.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage	Use stage							End of life stage			Benefits and loads beyond the system boundaries		
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m² Glass Wall System PureView

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	5.03E+01	1.94E-01	2.04E+00	0	9.06E-02	1.56E+00	1.81E-01	-1.74E+01
GWP-fossil	kg CO ₂ eq	5.24E+01	1.86E-01	3.94E-02	0	8.69E-02	1.56E+00	1.79E-01	-1.73E+01
GWP-biogenic	kg CO ₂ eq	-2.15E+00	8.07E-03	2E+00	0	3.77E-03	-8.46E-06	5.7E-04	-5.91E-02
GWP-luluc	kg CO ₂ eq	1.44E-02	7.25E-06	8.57E-06	0	3.39E-06	1.01E-04	1.08E-03	-1.86E-03
ODP	kg CFC11 eq	1.37E-10	1.62E-14	2.27E-13	0	7.57E-15	5.68E-13	4.84E-13	-1.49E-10
AP	mol H ⁺ eq	2.9E-01	2.05E-04	9.91E-04	0	9.57E-05	2.64E-04	1.27E-03	-6.44E-02
EP-freshwater	kg P eq	4.07E-05	4.74E-08	5.37E-08	0	2.21E-08	1.32E-07	4.08E-07	-9.3E-06
EP-marine	kg N eq	6.26E-02	7.31E-05	4.72E-04	0	3.42E-05	5.83E-05	3.28E-04	-7.79E-03
EP-terrestrial	mol N eq	7.04E-01	8.3E-04	5.46E-03	0	3.88E-04	1.22E-03	3.61E-03	-8.45E-02
POCP	kg NMVOC eq	1.58E-01	2.14E-04	1.22E-03	0	1E-04	1.63E-04	1E-03	-2.48E-02
ADPE	kg Sb eq	1.33E-04	4.82E-09	2.47E-09	0	2.25E-09	5.14E-09	1.16E-08	-4.76E-06
ADPF	MJ	6.96E+02	2.59E+00	5.95E-01	0	1.21E+00	7.77E-01	2.37E+00	-2.53E+02
WDP	m ³ world eq deprived	1.35E+01	3.73E-04	2.09E-01	0	1.74E-04	1.46E-01	2.05E-02	-8.03E-01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m² Glass Wall System PureView

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	2.68E+02	1.25E-02	1.61E+01	0	5.83E-03	2.8E-01	4.13E-01	-1.26E+02
PERM	MJ	1.6E+01	0	-1.6E+01	0	0	0	0	0
PERT	MJ	2.84E+02	1.25E-02	1.4E-01	0	5.83E-03	2.8E-01	4.13E-01	-1.26E+02
PENRE	MJ	6.86E+02	2.59E+00	5.95E-01	0	1.21E+00	1.14E+01	2.37E+00	-2.53E+02
PENRM	MJ	1.06E+01	0	0	0	0	-1.06E+01	0	0
PENRT	MJ	6.96E+02	2.59E+00	5.95E-01	0	1.21E+00	7.77E-01	2.37E+00	-2.53E+02
SM	kg	2.08E+00	0	0	0	0	0	0	3E+00
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
FW	m ³	4.88E-01	1.52E-05	4.91E-03	0	7.11E-06	3.51E-03	6.27E-04	-2.11E-01

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 m² Glass Wall System PureView

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	8.85E-07	7.99E-11	2.95E-10	0	3.73E-11	6.33E-10	5.9E-10	-9.71E-08
NHWD	kg	1.37E+01	2.48E-04	1.52E-02	0	1.16E-04	1.56E-01	1.2E+01	-4.49E+00
RWD	kg	3.26E-02	2.88E-06	2.65E-05	0	1.35E-06	2.45E-05	2.49E-05	-2.94E-02
CRU	kg	0	0	0	0	0	0	0	0
MFR	kg	1.53E+00	0	0	0	0	3.95E+00	0	0
MER	kg	0	0	0	0	0	0	0	0
EEE	MJ	0	0	2.3E+00	0	0	2.39E+00	0	0
EET	MJ	0	0	4.09E+00	0	0	5.54E+00	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:

1 m² Glass Wall System PureView

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	3.63E-06	1.88E-09	2.96E-09	0	8.76E-10	3.04E-09	1.6E-08	-1.06E-06
IR	kBq U235 eq	3.48E+00	3.95E-04	4.19E-03	0	1.84E-04	2.6E-03	2.88E-03	-5.93E+00
ETP-fw	CTUe	4.21E+02	1.92E+00	1.98E-01	0	8.97E-01	2.97E-01	1.36E+00	-5.83E+01
HTP-c	CTUh	6.04E-08	3.47E-11	1.46E-11	0	1.62E-11	2.42E-11	3.22E-11	-4.75E-09
HTP-nc	CTUh	3.73E-07	1.09E-09	2.35E-10	0	5.09E-10	1.83E-09	1.24E-09	-1.01E-07
SQP	SQP	1.64E+02	8.93E-03	1.52E-01	0	4.17E-03	2.56E-01	6.52E-01	-8.97E+00

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

This EPD was created using a software tool.

References

ADA

Americans with Disabilities Act 1990
<https://www.ada.gov/>

Sphera LCA for Experts, LCA FE,

Software system and databases,

Managed LCA content MLC (fka GaBi database),

University of Stuttgart and Sphera Solutions GmbH

STC

Sound Transmission Class
<https://asastandards.org/terms/sound-transmission-class/>

MLC documentation

MLC life cycle inventory data documentation
<https://lcadatabase.sphera.com/>

EN 15804

EN 15804:2012+A1 2013, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

LCA-tool dormakaba
 Tool No.: IBU-DOR-202508-LT2-EN
 Developed by Sphera Solutions GmbH

PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report according to EN15804+A2:2019, Version 1.4, 2024, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

PCR Part B

PCR – Part B: Requirements on the EPD for Room partition systems, version 08/2021, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

ISO 14025

EN ISO 14025:2011, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

The literature referred to in the Environmental Product Declaration must be listed in full. Standards already fully quoted in the EPD do not need to be listed here again. The current version of PCR Part A and PCR Part B of the PCR document on which they are based must be referenced.

Further References

IBU 2021

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021. www.ibu-epd.com.

SPHERA LCA FE

Publisher



Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

Programme holder



Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

Author of the Life Cycle Assessment



dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

+49 2333 793-0
info.de@dormakaba.com
www.dormakaba.com

Owner of the Declaration



Modernfold Inc.
West New Road 215
46140 Greenfield, IN
United States

+1 8008699685
info@modernfold.com
www.modernfold.com