

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804




| | |
|--------------------------|--------------------------------------|
| Owner of the Declaration | dormakaba International Holding GmbH |
| Programme holder | Institut Bauen und Umwelt e.V. (IBU) |
| Publisher | Institut Bauen und Umwelt e.V. (IBU) |
| Declaration number | EPD-DOR-20160276-ICA1-EN |
| Issue date | 24.04.2017 |
| Valid to | 23.04.2023 |

Automatic Revolving Door KTC 2 dormakaba

www.ibu-epd.com / <https://epd-online.com>



1. General Information

| | |
|---|---|
| dormakaba Programme holder IBU - Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany | Automatic Revolving Door KTC 2 Owner of the Declaration dormakaba International Holding GmbH DORMA Platz 1 58256 Ennepetal Deutschland |
| Declaration number EPD-DOR-20160276-ICA1-EN | Declared product / Declared unit The declaration represents one automatic revolving door, consisting of two (2) door leaves and an integrated sliding door. The revolving door has a diameter of 4800 mm and a height of 2200 mm. |
| This Declaration is based on the Product Category Rules: Automatic doors, automatic gates, and revolving door systems, 07.2014 (PCR tested and approved by the SVR) | Scope: The declaration and background LCA report represent dormakaba's KTC 2 automatic revolving doors. Raw materials and components are provided by suppliers and shipped to dormakaba's facility in Suzhou, China. Doors are manufactured and assembled at the facility before being shipped to job sites. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences. |
| Issue date 24.04.2017 | Verification The CEN Norm /EN 15804/ serves as the core PCR Independent verification of the declaration according to /ISO 14025/ <input type="checkbox"/> internally <input checked="" type="checkbox"/> externally |
| Valid to 23.04.2023  Prof. Dr.-Ing. Horst J. Bossenmayer (President of Institut Bauen und Umwelt e.V.) |  Dr.-Ing. Wolfram Trinius (Independent verifier appointed by SVR) |
|  Dr. Burkhard Lehmann (Managing Director IBU) | |

2. Product

2.1 Product description / Product definition

The revolving doors of the COMFORTLINE (KTC) series combine safety and comfort in a sophisticated entrance system.

KTC series doors help to protect building interiors from drafts, noise and dirt. In minimizing airflow between the outside and inside, a revolving door will usually pay for itself in energy savings. KTC series revolving doors help pedestrians move in and out of the building and manage high traffic volumes without difficulty. And all KTC series doors offer ultra-modern safety and security systems for your peace of mind.

The two-wing revolving door KTC 2 is the perfect solution for high user convenience, varied traffic flow and a need for increased environmental control. The integrated sliding doors allow for both winter and summer use giving optimum performance throughout the year. This intelligent revolving door with its automatic sliding door—integrated in the system's turnstile—optimizes user traffic and at the same time reliably protects from external influences. Special brush seals help to create a sensible climate barrier between the interior and the exterior of the building.

This feature helps to reduce heating or air conditioning costs and the drive motor itself offers a low energy consumption.

Further benefits are:

- Spacious entrance
- Easy passage of bulky items
- Suitable for disabled users
- Large sections
- Integrated night shield
- Showcases for advertising purpose
- Highest safety standards
- Redundant design for compliance with various national escape route requirements

For placing of the product on the market in the EU/EFTA (with the exception of Switzerland), the following legal provisions apply:

- /EMC Directive/ (2014/30/EU)
- /Machinery Directive/ (2006/42/EC)

as well as the harmonized norms based on these provisions:

- /DIN EN ISO 13849-1/: Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design.
- /DIN EN ISO 12100/: Safety of machinery - Basic concepts - Risk assessment and risk reduction.
- /DIN EN 16005/: Power operated pedestrian doorsets - Safety in use - Requirements and test methods.
- /DIN EN 61000 - 6 - 2/: Electromagnetic compatibility (EMC). Part 6-2: Generic standards: Interference resistance for industrial environments.
- /DIN EN 61000 - 6 - 3/: Electromagnetic compatibility (EMC). Part 6-3: Generic standards: Emission standard for residential, commercial and light-industrial environments.
- /DIN EN 61000 - 3 - 2/: Electromagnetic compatibility-3-2: Limits - Limits for harmonic current emissions.
- /DIN EN 61000 - 3 - 3/: Electromagnetic compatibility-3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems.
- /DIN EN 55022/: Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement.
- /DIN EN ISO 9001/: Quality management systems.
- /DIN EN 60335 - 1/: Safety of household and similar electrical appliances. Part 1: General requirements.
- /EN 60335-2-103/: Household and similar electrical appliances. Safety. Particular requirements for drives for gates, doors and windows.
- /IEC 60335-2-103/: Household and similar electrical appliances. Safety. Part 2-103: Particular requirements for drives for gates, doors and windows.

The CE-marking takes into account the proof of conformity with the respective harmonized norms based on the legal provisions above. For the application and use, the respective national provisions apply.

In addition to the harmonized standards, the following national standards have also been applied and complied with:

- /DIN 18650-1/: Powered pedestrian doors. Part 1: Product requirements and test methods.
- /DIN 18650-2/: Powered pedestrian doors. Part 2: Safety at powered pedestrian doors.
- /AutSchR/.

- /ASR A1.7/: Technical rules for the workplace. Doors and gates.

2.2 Application

Automatic revolving doors may be used to provide a comfortable entry and exit in many applications in the facade of or within a building.

Typical applications include:

- Hotels
- Healthcare settings
- Airports and transportation facilities
- Commercial office buildings
- Institutional and educational buildings
- Retail stores

2.3 Technical Data

Performance data of the product according to the harmonized norms, based on the harmonization provisions. The following technical data also apply:

| Name | Value | Unit |
|---------------------------|-------|------|
| Power input "Standby"** | 70 | W |
| Power input "Operation"** | 198 | W |

**excludes lighting

2.4 Delivery status

A fully automatic revolving door with the following dimensions:

- Internal diameter: 4800 mm
- External diameter: 4892 mm
- Clear passage height: 2200 mm

The unit is delivered ready for installation.

2.5 Base materials / Ancillary materials

The basic material composition of the door is given below. The door includes both aluminum and steel components.

| Name | Value | Unit |
|--------------------------|-------|------|
| Glass | 34 | % |
| Aluminum | 31 | % |
| Stainless & carbon steel | 23 | % |
| Chipboard | 6 | % |
| Plastics | 3 | % |
| Electronics | 3 | % |

2.6 Manufacture

Materials such as aluminum sheet, steel bar, and tempered glass are shipped to dormakaba in Suzhou, China, where they are further processed into door leafs and other components. Depending on the component, some aluminum parts are powder coated. The door is then packaged in wooden crates and shipped to the job site for installation.

The plant in Suzhou, China is certified to the quality

management system /ISO 9001/, which ensures consistent quality of dormakaba's products.

2.7 Environment and health during manufacturing

The manufacturing plant has an internal environmental, health and safety engineer and an integrated system according to national regulations and good European practices. The system ensures healthful and safe workplaces and good working conditions for each employee.

The dormakaba environmental management system at the Suzhou, China facility is certified to /ISO 14001/.

2.8 Product processing/Installation

Cutters, sanders, drills, and other standard equipment are used to manufacture the door. Ancillary materials include supplies for this equipment.

Installation is done manually with simple tools.

2.9 Packaging

Packaging is intended to protect the product during distribution. Wood crates are used to package larger components, while corrugate is used for the accessories.

2.10 Condition of use

Regular maintenance is advised to ensure the life expectancy of 15 years. Sensors, weather stripping, and other components are assumed to be replaced halfway through the service life.

2.11 Environment and health during use

No impacts on human health or the environment are expected during product use.

2.12 Reference service life

The reference lives of dormakaba's automatic revolving doors will ultimately depend on the traffic pattern and degree of usage of the doors. A reference service life of 15 years is assumed for calculation of the Use Stage impacts of the KTC 2 door. This is consistent with approximately 10 million cycles over the door's service life.

2.13 Extraordinary effects

Fire

Not applicable.

Water

Unforeseen contact with water may result in a malfunction of the electronic components if the IP rating of the components is exceeded.

Should contact with water occur, the unit is designed to remain in a fail-safe state and is not anticipated to cause impact to the environment.

Mechanical destruction

No impacts on human health or the environment are known or expected. No hazardous substance emissions are anticipated in case of mechanical destruction.

2.14 Re-use phase

Reuse of individual product components is not anticipated. The door, however, can be disassembled and individual materials such as aluminum, steel, and glass recycled. Plastic components can be combusted for energy recovery.

2.15 Disposal

Manufacturing

Scrap from production is collected separately by material type and disposed of.

- /EWC 12 01 01/ Ferrous metal filings and turnings
- /EWC 12 01 03/ Non-ferrous metal filings and turnings

Packaging

Packaging waste from installation is assumed to be disposed to landfill.

- /EWC 15 01 01/ Paper and cardboard packaging
- /EWC 15 01 02/ Plastic packaging
- /EWC 15 01 03/ Wooden packaging

End-of-life

Door components at end-of-life can be either sent for material or energy recovery, or disposed to landfill. Recovery rates will depend on typical practices at the location in which the door is installed.

- /EWC 17 02 02/ Glass
- /EWC 17 03 03/ Plastic
- /EWC 17 04 01/ Copper, bronze, brass
- /EWC 17 04 02/ Aluminum
- /EWC 17 04 05/ Iron and steel
- /EWC 17 04 11/ Cables with the exception of those outlined in 17 04 10

2.16 Further information

Please refer to the last page of this declaration for contact details to obtain further information.

3. LCA: Calculation rules

3.1 Declared Unit

The declared unit for this analysis is one (1) revolving door system.

Declared unit

| Name | Value | Unit |
|--|-------|----------------|
| Declared unit for revolving door system* | 10.6 | m ² |
| Mass of the entire system | 2911 | kg |

| | | |
|---|---------|-------------------|
| Conversion factor to 1 kg | 0.00034 | - |
| Grammage of the components | 276 | kg/m ² |
| Dimensions for revolving door, diameter | 4800 | mm |
| Dimensions for revolving door, height | 2200 | mm |

* Area represents the cross-sectional area of the door, which is designed to fit in an opening of 4800-mm wide by 2200-mm high.

3.2 System boundary

Type of EPD: cradle-to-grave. The following modules were considered in this analysis:

Product stage

- Raw material supply (A1)
- Transport (A2)
- Manufacturing (A3)

Construction stage

- Transport to the building site (A4)
- Installation, including packaging disposal (A5)

Use stage

- Maintenance (B2)
- Operation energy use (B6)

End-of-life stage

- Transport to disposal (C2)
- Waste processing (C3)
- Disposal (C4)

Benefits and loads beyond the system boundary

- Reuse, recovery, and recycling potential (D)

Submodules that were not declared either do not apply and would therefore be zero, or are estimated to fall below the cut-off criteria.

3.3 Estimates and assumptions

Door use stage energy consumption was calculated assuming that doors are in use 255 working days per year and switched off for the remaining 110 non-working days per year. Additionally, during each work day, doors were assumed to be actively working 6 hours per day, in idle mode 10 hours per day, and switched off 8 hours per day.

Revolving doors installation, maintenance, and deconstruction were assumed to be performed by hand with minimal additional electricity required to operate power tools.

3.4 Cut-off criteria

All available data from the production process are considered in the analysis. This includes raw materials

used, thermal energy, electric power consumption, and ancillary materials

3.5 Background data

The LCA model was created using the GaBi ts Software system for life cycle engineering, developed by thinkstep AG /thinkstep 2016/. The GaBi 2016 LCI database /thinkstep 2016b/ provides the life cycle inventory data for most of the raw and process materials obtained from the background system.

3.6 Data quality

Primary materials and production data were obtained directly from dormakaba's facilities that produce KTC 2 doors. Background data were sourced from the GaBi 2016 database /thinkstep 2016b/ and are representative of the years 2007 - 2015. Chinese or global data were used as appropriate. Where Chinese data were not available, proxy data representing the same technology from another country or region were used. In general, geographical and technological representativeness is warranted. Primary data were also evaluated for precision, completeness, and consistency, including cross-checks with other sources. Overall, data are considered to be of high quality.

3.7 Period under review

The period under review is the 2014/2015 fiscal year.

3.8 Allocation

Manufacturing inputs (e.g. ancillary materials, packaging, and energy) were allocated on a per-door basis.

Material credits attributed to Module D were calculated based on the net amount of scrap leaving the system boundary (i.e., the amount of scrap generated upon disposal, minus the amount of scrap consumed by raw material production).

3.9 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

4. LCA: Scenarios and additional technical information

Additional information is provided for the declared modules, including A4, A5, B2, B6, C2, C4, and D. In order to represent dormakaba's global distribution network, sales-weighted averages are used to model transport to the building sites and electricity consumption during product use.

Transport to the building site (A4)

| Name | Value | Unit |
|---|-------|---------|
| Litres of fuel | 23 | l/100km |
| Transport distance | 8580 | km |
| Capacity utilisation (including empty runs) | 51 | % |

Installation into the building (A5)

| Name | Value | Unit |
|-------------------------------------|-------|------|
| Packaging waste for disposal (wood) | 173 | kg |

| | | |
|--------------------------------------|-----|----|
| Packaging waste for disposal (other) | 0.6 | kg |
|--------------------------------------|-----|----|

Maintenance (B2)

| Name | Value | Unit |
|------------------------|-------|-------------|
| Maintenance cycle | 1 | Number/R SL |
| Replacement components | 49 | kg |

Reference service life

| Name | Value | Unit |
|------------------------|-------|------|
| Reference service life | 15 | a |

Operational energy use (B6) and Operational water use (B7)

| Name | Value | Unit |
|-------------------------|-------|------|
| Electricity consumption | 12100 | kWh |

End of life (C1-C4)

| Name | Value | Unit |
|---------------------------------------|-------|------|
| Collected separately | 1370 | kg |
| Collected as mixed construction waste | 1540 | kg |
| Recycling | 1370 | kg |
| Landfilling | 1540 | kg |

Reuse, recovery and/or recycling potentials (D), relevant scenario information

| Name | Value | Unit |
|---------------------------|-------|------|
| Collection rate, aluminum | 90 | % |
| Collection rate, steel | 81 | % |

5. LCA: Results

The table below summarizes which modules are declared and which are not declared. Environmental performance results are shown for one (1) piece of revolving door and represent the average of KTC 2 doors produced at dormakaba's facility.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

| PRODUCT STAGE | | | CONSTRUCTION PROCESS STAGE | | USE STAGE | | | | | | | END OF LIFE STAGE | | | | BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES |
|---------------------|-----------|---------------|-------------------------------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|---|
| Raw material supply | Transport | Manufacturing | Transport from the gate to the site | Assembly | Use | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential |
| A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| X | X | X | X | X | MND | X | MNR | MNR | MNR | X | MND | MND | X | X | X | X |

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: one revolving door system

| Parameter | Unit | A1-A3 | A4 | A5 | B2 | B6 | C2 | C3 | C4 | D |
|-----------|---|---------|----------|----------|---------|---------|----------|---------|----------|----------|
| GWP | [kg CO ₂ -Eq.] | 2.65E+4 | 6.12E+2 | 2.96E+2 | 7.83E+2 | 1.02E+4 | 4.14E+1 | 0.00E+0 | 1.13E+2 | -1.50E+4 |
| ODP | [kg CFC11-Eq.] | 3.20E-6 | 4.33E-11 | 4.65E-10 | 1.14E-7 | 9.46E-7 | 3.15E-12 | 0.00E+0 | 3.69E-10 | 1.45E-5 |
| AP | [kg SO ₂ -Eq.] | 1.24E+2 | 1.17E+1 | 7.22E-2 | 4.80E+0 | 4.29E+1 | 1.61E-1 | 0.00E+0 | 1.53E-1 | -1.21E+2 |
| EP | [kg (PO ₄) ³ -Eq.] | 8.98E+0 | 1.31E+0 | 2.36E-1 | 3.15E-1 | 3.03E+0 | 3.60E-2 | 0.00E+0 | 1.02E-1 | -9.99E+0 |
| POCP | [kg ethene-Eq.] | 9.50E+0 | 2.85E-1 | 7.03E-2 | 3.08E-1 | 3.82E+0 | -5.36E-2 | 0.00E+0 | 3.55E-2 | -7.90E+0 |
| ADPE | [kg Sb-Eq.] | 2.78E-1 | 2.13E-5 | 2.52E-6 | 7.18E-2 | 8.95E-4 | 1.54E-6 | 0.00E+0 | 8.56E-6 | -4.52E-2 |
| ADPF | [MJ] | 3.19E+5 | 8.15E+3 | 2.12E+2 | 9.97E+3 | 1.05E+5 | 5.69E+2 | 0.00E+0 | 3.63E+2 | -1.42E+5 |

Caption: GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

RESULTS OF THE LCA - RESOURCE USE: one revolving door system

| Parameter | Unit | A1-A3 | A4 | A5 | B2 | B6 | C2 | C3 | C4 | D |
|-----------|------|---------|---------|---------|---------|---------|---------|---------|---------|----------|
| PERE | [MJ] | 1.33E+4 | 2.79E+1 | 1.28E+1 | 1.46E+3 | 1.66E+4 | 2.70E+0 | 0.00E+0 | 3.52E+1 | -2.45E+4 |
| PERM | [MJ] | 3.22E+3 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 |
| PERT | [MJ] | 1.65E+4 | 2.79E+1 | 1.28E+1 | 1.46E+3 | 1.66E+4 | 2.70E+0 | 0.00E+0 | 3.52E+1 | -2.45E+4 |
| PENRE | [MJ] | 3.23E+5 | 8.15E+3 | 2.19E+2 | 1.09E+4 | 1.17E+5 | 5.70E+2 | 0.00E+0 | 3.76E+2 | -1.45E+5 |
| PENRM | [MJ] | 4.52E+3 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 |
| PENRT | [MJ] | 3.28E+5 | 8.15E+3 | 2.19E+2 | 1.09E+4 | 1.17E+5 | 5.70E+2 | 0.00E+0 | 3.76E+2 | -1.45E+5 |
| SM | [kg] | 2.26E+2 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 |
| RSF | [MJ] | 7.89E-2 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | -7.68E+0 |
| NRSF | [MJ] | 6.89E-1 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | -7.45E+1 |
| FW | [m³] | 1.40E+3 | 8.29E-2 | 3.79E-2 | 5.51E+0 | 7.68E+1 | 7.66E-3 | 0.00E+0 | 5.78E-2 | -9.81E+1 |

Caption: PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES: one revolving door system

| Parameter | Unit | A1-A3 | A4 | A5 | B2 | B6 | C2 | C3 | C4 | D |
|-----------|------|---------|---------|---------|---------|---------|---------|---------|---------|----------|
| HWD | [kg] | 7.82E-2 | 3.77E-6 | 1.07E-6 | 1.04E-4 | 1.17E-4 | 2.64E-7 | 0.00E+0 | 1.34E-6 | -1.57E+0 |
| NHWD | [kg] | 2.74E+3 | 6.82E-2 | 1.03E+2 | 9.06E+1 | 4.42E+1 | 5.54E-3 | 0.00E+0 | 1.46E+3 | -2.45E+3 |
| RWD | [kg] | 2.40E+0 | 1.97E-3 | 2.83E-3 | 3.80E-1 | 4.71E+0 | 1.52E-4 | 0.00E+0 | 5.14E-3 | -1.18E+0 |
| CRU | [kg] | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 |
| MFR | [kg] | 3.12E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 1.30E+3 | 0.00E+0 | 0.00E+0 |
| MER | [kg] | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 |
| EEE | [MJ] | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 |
| EET | [MJ] | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 | 0.00E+0 |

Caption: HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EEE = Exported thermal energy

6. LCA: Interpretation

The revolving door environmental footprint is dominated by materials production (Module A1), followed by electricity consumption during door operation (Module B6). Materials used during door

maintenance also play a notable role, in particular for abiotic depletion potential of elements. Module D is associated with a net positive ozone depletion potential (i.e., an environmental burden) due to differences in

furnace technologies used to produce primary and secondary steel.

At the end-of-life, the metal components of the revolving door are modeled as being recycled. A

portion of the aluminum, steel, and bronze are recovered and the remainder landfilled. Glass, however, is assumed to be sent entirely to landfill as recycling this material from demolished buildings is not considered common practice.

7. Requisite evidence

Not applicable.

8. References

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.):
Generation of Environmental Product Declarations (EPDs);
www.ibu-epd.de

ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 15804

EN 15804:2012-04+A1 2013: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

EMC Directive

Directive 2014/30/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 2004/108/EC.

Machinery Directive

Directive 2006/42/EC of the European Parliament and of the Council of 17 May 2006 on machinery, and amending Directive 95/16/EC.

ISO 9001

Quality management systems - Requirements (ISO 9001:2008).

ISO 14001

Environmental management system (ISO 14001:2015).

EWC

European Waste Catalogue.

thinkstep 2016

thinkstep; GaBi ts: Software-System and Database for Life Cycle Engineering. Copyright, TM. Stuttgart, Echterdingen, 1992-2016.

thinkstep 2016b

GaBi ts: Documentation of GaBi ts: Software-System and Database for Life Cycle Engineering. Copyright, TM. Stuttgart, Echterdingen, 1992-2016.
<http://www.gabi-software.com/international/databases/gabi-databases/>.

ISO 14040

EN ISO 14040:2006, Environmental management - Life cycle assessment - Principles and framework.

ISO 14044

EN ISO 14044:2006, Environmental management - Life cycle assessment - Requirements and guidelines.

PCR Part A

Institut Bauen und Umwelt e.V., Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. 2013. www.ibu-epd.com.

PCR Part B

PCR Guidance-Texts for Building-Related Products and Services. From the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU). Part B: Requirements on the EPD for automatic doors, automatic gates, and revolving door systems. 2012. www.ibu-epd.com.

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 - 3087748 - 29
Mail info@ibu-epd.com
Web www.ibu-epd.com



thinkstep

**Author of the Life Cycle
Assessment**

thinkstep, Inc.
Milk Street 170
02109 Boston, MA
United States

Tel +1 617 247 4477
Fax +1 857 400 9454
Mail info@thinkstep.com
Web www.thinkstep.com

**Owner of the Declaration**

dormakaba International Holding
GmbH
DORMA Platz 1
58256 Ennepetal
Germany

Tel +49 2333 793-0
Fax +49 2333 793-4950
Mail info.de@dormakaba.com
Web www.dormakaba.com