

TS 68 and TS 69 Scissor Arm Door Closer

Key Figures

Lifetime per unit: 20 years
Weight per unit: 2 kg
Production location: Suzhou, China

Production standards


Quality	Environmental	Occupational Health & Safety	Energy	Produced with green electricity
ISO 9001 certified				

Product declarations

Environmental Product Declaration	Health Product Declaration	Building Product Declaration	SuPIM Data Sheet
✓	✓		


Material used (%)

Steel Aluminium Paper Plastic Oil



The GWP¹ across the life cycle is 13 kg CO₂e

This is similar to the CO₂ produced from a road trip with a diesel mid-range car from Ennepetal to Dortmund airport



¹ Carbon dioxide equivalent (CO₂e) is the universal unit of measurement to indicate the global warming potential (GWP) of each of the six greenhouse gases, expressed in terms of the GWP of one unit of carbon dioxide. It is used to evaluate releasing (or avoiding releasing) different greenhouse gases against a common basis.



Scan the QR code or click here for more information about sustainability



Scan the QR code or click here for more information about our sustainability product declaration.



Description

The TS 68 and TS 69 are low-cost door closers which can be universally used on all common door types. The door closers are particularly quick and easy to install. For the use and application of the product the respective national provisions at the place of use apply. The door closers are used for any standard door and almost all mounting position.

Total Global Warming Potential per life cycle stage (kg CO₂e)

