

# ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

|                          |                                      |
|--------------------------|--------------------------------------|
| Owner of the Declaration | dormakaba International Holding GmbH |
| Publisher                | Institut Bauen und Umwelt e.V. (IBU) |
| Programme holder         | Institut Bauen und Umwelt e.V. (IBU) |
| Declaration number       | EPD-DOR-20240264-CBA1-EN             |
| Issue date               | 29.11.2024                           |
| Valid to                 | 28.11.2029                           |

## Door closer TS Kompakt dormakaba

[www.ibu-epd.com](http://www.ibu-epd.com) | <https://epd-online.com>



General Information

dormakaba

Programme holder

IBU – Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

Declaration number

EPD-DOR-20240264-CBA1-EN

This declaration is based on the product category rules:

Building Hardware products, 01.08.2021  
(PCR checked and approved by the SVR)

Issue date

29.11.2024

Valid to

28.11.2029



Dipl.-Ing. Hans Peters  
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold  
(Managing Director Institut Bauen und Umwelt e.V.)

Door closer TS Kompakt

Owner of the declaration

dormakaba International Holding GmbH  
DORMA Platz 1  
58256 Ennepetal  
Germany

Declared product / declared unit

1 piece of the product: Door closer TS Kompakt consisting of the following items:

- 1 door closer
- Product packaging

Scope:

This Environmental Product Declaration refers to a specific door closer manufactured by dormakaba. The production site is located in Suzhou (China).


The data represents the year 2022.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

|  |            |  |
|--|------------|--|
| The standard EN 15804 serves as the core PCR                                     |            |  |
| Independent verification of the declaration and data according to ISO 14025:2011 |            |  |
| <input type="checkbox"/>   | internally | <input checked="" type="checkbox"/> externally |



Matthias Klingler,  
(Independent verifier)

## Product

### Product description/Product definition

With the door closer TS Kompakt, dormakaba has developed a door closer which can be universally used on all common door types. It is particularly quick and easy to install – and does not require a mounting backplate. Changes in templating allow easy selection of the closing force to suit various door sizes.

For the use and application of the product the respective national provisions at the place of use apply. For the door closer TS Kompakt the standards which can be applied are the following:

- EN 1634-1
- UL 10c

...

### Application

The door closer TS Kompakt is the ideal solution for standard doors.

### Technical Data

The door closer TS Kompakt has following technical properties:

| Name                | Value       | Unit       |
|---------------------|-------------|------------|
| Closing force       | 2/3/4       | adjustable |
| For standard doors  | 1100        | mm         |
| Non-handed          | NA          | standard   |
| Hold-open function  | NA          | optional   |
| Closing speed       | NA          | adjustable |
| Closing speed range | 180-15/15-0 | degrees    |

Performance data of the product with respect to its characteristics in accordance with the relevant

technical provision which can be applied are mentioned above.

### Base materials/Ancillary materials

The major material composition including the packaging of the product is listed below:

| Name      | Value | Unit |
|-----------|-------|------|
| Steel     | 61    | %    |
| Aluminium | 25    | %    |
| Lubricant | 7     | %    |
| Packaging | 5     | %    |
| Plastics  | <1    | %    |
| Paper     | <1    | %    |

The product includes partial articles which contain substances listed in the *Candidate List of REACH Regulation 1907/2006/EC* (date: 14.06.2023) exceeding 0.1 percentage by mass: yes

- Lead (Pb): 7439-92-1 (CAS-No.) is included in some of the alloys used. The concentration of lead in each individual alloy does not exceed 4% (by mass).

The *Candidate List* can be found on the *ECHA* website address: <https://echa.europa.eu/de/home>.

### Reference service life

The reference service life of the door closer TS Kompakt amounts to 10 years, depending on the application and frequency of use. For repairs and renewals, suitable spare parts are available. The door closer is tested and certified to *UL10c*, meaning they are designed to withstand a minimum of 100,000 cycles.

## LCA: Calculation rules

### Declared Unit

The declared unit is 1 piece of the product: Door closer TS Kompakt including packaging

| Name                                       | Value | Unit          |
|--|-------|---------------|
| Declared unit                              | 1     | piece/product |
| Mass of declared product without packaging | 1.23  | kg            |
| Mass of packaging                          | 0,07  | kg            |

### System boundary

The type of EPD is: cradle to gate with options, modules C1–C4, and module D (A1–A3 + C + D and additional modules: A4+ A5)

### Production - Module A1-A3

The product stage includes: — A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes), — A2, transport to the manufacturer, — A3, manufacturing and assembly including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state.

### Construction stage - Modules A4-A5

The construction process stage includes:

— A4, transport to the building site; — A5, installation into the building; including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction process stage.

### End-of-life stage– Modules C1-C4 and D

The end-of-life stage includes: — C1, de-construction, demolition; — C2, transport to waste processing; — C3, waste processing for reuse, recovery and/or recycling; — C4, disposal; including provision and all transport, provision of all materials, products and related energy and water use. Module D (Benefits and loads beyond the system boundary) includes: — D, recycling potentials, expressed as net impacts and benefits.

### Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Global

### Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Background database: GaBi, SP40.

## LCA: Scenarios and additional technical information

### Characteristic product properties of biogenic carbon

| Name  | Value | Unit |
|---|-------|------|
| Biogenic carbon content in product                | -     | kg C |
| Biogenic carbon content in accompanying packaging | 0.03  | kg C |

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO<sub>2</sub>.

Suzhou (China) is considered for A3.

### Transport to the building site (A4)

| Name  | Value   | Unit    |
|---|---------|---------|
| Litres of fuel  | 0.00276 | l/100km |
| Capacity utilisation (including empty runs)                             | 55      | %       |
| Transport distance (ship)   | 10000   | km      |
| Transport distance via truck (from harbor to dormakaba logistic centre) | 500     | km      |
| Transport distance via truck (for scaling)                              | 100     | km      |

The product is transported via truck and ship. The main distribution regions are Asia and the EU (Russia). For Asia and Russia, the product is stored in China with the calculated transport distances. For the rest of Europe, the product is stored in the dormakaba logistic center in Germany. In order to allow scaling to a specific point of installation 100 km is declared as well.

### Installation into the building (A5)

| Name                                | Value | Unit |
|-------------------------------------|-------|------|
| Waste packaging (paper and plastic) | 0.07  | kg   |

### Reference service life

| Name                                    | Value | Unit |
|---|-------|------|
| Life Span according to the manufacturer | 10    | a    |

### End of life (C1-C4)

C1: The product dismantling from the building is done manually without environmental burden.

C2: Transport to waste management is 50 km.

| Name                            | Value  | Unit |
|---------------------------------|--------|------|
| Collected separately waste type | 1.23   | kg   |
| Recycling                       | 1.23   | kg   |
| Energy recovery                 | 0.0017 | kg   |

The product is disassembled in a recycling process. Material recycling is then assumed for metals. The plastic components are assumed to be incinerated with energy recovery. Region for the End of Life is: Global.

### Reuse, recovery and/or recycling potentials (D), relevant scenario information

| Name      | Value | Unit |
|-----------|-------|------|
| Recycling | 100   | %    |

The collection rate is 100 %.

## LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

| Product stage       |           |               | Construction process stage          |          | Use stage |             |        |             |               |                        |                       | End of life stage          |           |                  |          | Benefits and loads beyond the system boundaries |
|---------------------|-----------|---------------|-------------------------------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|---|
| Raw material supply | Transport | Manufacturing | Transport from the gate to the site | Assembly | Use       | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential              |
| A1                  | A2        | A3            | A4                                  | A5       | B1        | B2          | B3     | B4          | B5            | B6                     | B7                    | C1                         | C2        | C3               | C4       | D   |
| X                   | X         | X             | X                                   | X        | MND       | MND         | MNR    | MNR         | MNR           | MND                    | MND                   | X                          | X         | X                | X        | X   |

### RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 piece TS Kompakt

| Parameter      | Unit                             | A1-A3     | A4       | A5       | C1 | C2       | C3       | C4 | D         |
|----------------|----------------------------------|-----------|----------|----------|----|----------|----------|----|-----------|
| GWP-total      | kg CO <sub>2</sub> eq            | 1.15E+01  | 9.93E-02 | 9.81E-02 | 0  | 5.38E-03 | 2.22E-01 | 0  | -2.46E+00 |
| GWP-fossil     | kg CO <sub>2</sub> eq            | 1.17E+01  | 9.67E-02 | 2.46E-03 | 0  | 5.14E-03 | 2.11E-01 | 0  | -2.45E+00 |
| GWP-biogenic   | kg CO <sub>2</sub> eq            | -1.18E-01 | 2.57E-03 | 9.57E-02 | 0  | 2.38E-04 | 1.08E-02 | 0  | -7.48E-03 |
| GWP-luluc      | kg CO <sub>2</sub> eq            | 4.68E-03  | 2.17E-06 | 1.61E-06 | 0  | 1.22E-07 | 1.2E-05  | 0  | -4.13E-04 |
| ODP            | kg CFC11 eq                      | 2.3E-12   | 9.74E-18 | 1.77E-17 | 0  | 5.43E-19 | 1.08E-16 | 0  | -1.71E-11 |
| AP             | mol H <sup>+</sup> eq            | 5.42E-02  | 1.62E-03 | 2.75E-05 | 0  | 5.15E-06 | 3.91E-05 | 0  | -8.81E-03 |
| EP-freshwater  | kg P eq                          | 6.91E-06  | 2.12E-08 | 3.46E-09 | 0  | 1.1E-09  | 1.71E-08 | 0  | -1.44E-06 |
| EP-marine      | kg N eq                          | 9.06E-03  | 4.3E-04  | 9.92E-06 | 0  | 1.64E-06 | 8.97E-06 | 0  | -1.19E-03 |
| EP-terrestrial | mol N eq                         | 9.84E-02  | 4.72E-03 | 1.24E-04 | 0  | 1.82E-05 | 1.78E-04 | 0  | -1.29E-02 |
| POCP           | kg NMVOC eq                      | 2.79E-02  | 1.2E-03  | 2.63E-05 | 0  | 4.63E-06 | 2.48E-05 | 0  | -3.84E-03 |
| ADPE           | kg Sb eq                         | 1.29E-04  | 2.72E-09 | 2.79E-10 | 0  | 1.54E-10 | 1.48E-09 | 0  | -2.66E-05 |
| ADPF           | MJ                               | 1.19E+02  | 1.28E+00 | 3.1E-02  | 0  | 7.29E-02 | 1E-01    | 0  | -3.43E+01 |
| WDP            | m <sup>3</sup> world eq deprived | 2.19E+00  | 1.83E-04 | 1.22E-02 | 0  | 1.01E-05 | 2.27E-02 | 0  | -1.27E-01 |

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

### RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 piece TS Kompakt

| Parameter | Unit           | A1-A3    | A4       | A5       | C1 | C2       | C3        | C4 | D         |
|-----------|----------------|----------|----------|----------|----|----------|-----------|----|-----------|
| PERE      | MJ             | 1.63E+01 | 4.11E-03 | 8.36E-01 | 0  | 2.3E-04  | 9.78E-02  | 0  | -1.49E+01 |
| PERM      | MJ             | 9.02E-01 | 0        | -8.3E-01 | 0  | 0        | -7.2E-02  | 0  | 0         |
| PERT      | MJ             | 1.72E+01 | 4.11E-03 | 5.63E-03 | 0  | 2.3E-04  | 2.58E-02  | 0  | -1.49E+01 |
| PENRE     | MJ             | 1.19E+02 | 1.29E+00 | 3.1E-02  | 0  | 7.3E-02  | 1.2E-01   | 0  | -3.43E+01 |
| PENRM     | MJ             | 1.95E-02 | 0        | 0        | 0  | 0        | -1.95E-02 | 0  | 0         |
| PENRT     | MJ             | 1.19E+02 | 1.29E+00 | 3.1E-02  | 0  | 7.3E-02  | 1E-01     | 0  | -3.43E+01 |
| SM        | kg             | 7.18E-01 | 0        | 0        | 0  | 0        | 0         | 0  | 0         |
| RSF       | MJ             | 0        | 0        | 0        | 0  | 0        | 0         | 0  | 0         |
| NRSF      | MJ             | 0        | 0        | 0        | 0  | 0        | 0         | 0  | 0         |
| FW        | m <sup>3</sup> | 5.71E-02 | 7.42E-06 | 2.86E-04 | 0  | 4.12E-07 | 5.42E-04  | 0  | -2.64E-02 |

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

### RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 piece TS Kompakt

| Parameter | Unit | A1-A3    | A4       | A5       | C1 | C2       | C3       | C4 | D         |
|-----------|------|----------|----------|----------|----|----------|----------|----|-----------|
| HWD       | kg   | 1.68E-07 | 1.25E-10 | 4.57E-11 | 0  | 7.08E-12 | 3.74E-10 | 0  | -2.76E-07 |
| NHWD      | kg   | 1.36E+00 | 1.31E-04 | 3.07E-03 | 0  | 7.46E-06 | 2.2E-02  | 0  | -5.47E-01 |
| RWD       | kg   | 1.72E-03 | 1.4E-06  | 1.63E-06 | 0  | 7.83E-08 | 3.76E-06 | 0  | -3.61E-03 |
| CRU       | kg   | 0        | 0        | 0        | 0  | 0        | 0        | 0  | 0         |
| MFR       | kg   | 0        | 0        | 0        | 0  | 0        | 1.14E+00 | 0  | 0         |
| MER       | kg   | 0        | 0        | 0        | 0  | 0        | 0        | 0  | 0         |
| EEE       | MJ   | 0        | 0        | 1.48E-01 | 0  | 0        | 4.06E-01 | 0  | 0         |
| EET       | MJ   | 0        | 0        | 2.69E-01 | 0  | 0        | 9.24E-01 | 0  | 0         |

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

## RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:

### 1 piece TS Kompakt

| Parameter | Unit              | A1-A3    | A4       | A5       | C1 | C2       | C3       | C4 | D         |
|-----------|-------------------|----------|----------|----------|----|----------|----------|----|-----------|
| PM        | Disease incidence | 1.38E-06 | 2.7E-08  | 1.52E-10 | 0  | 2.7E-11  | 4.87E-10 | 0  | -1.4E-07  |
| IR        | kBq U235 eq       | 1.97E-01 | 2.01E-04 | 2.52E-04 | 0  | 1.12E-05 | 3.48E-04 | 0  | -7.19E-01 |
| ETP-fw    | CTUe              | 3.96E+01 | 9.09E-01 | 1.47E-02 | 0  | 5.17E-02 | 3.77E-02 | 0  | -1.21E+01 |
| HTP-c     | CTUh              | 3.94E-09 | 1.71E-11 | 7.77E-13 | 0  | 9.72E-13 | 3.24E-12 | 0  | -2.91E-10 |
| HTP-nc    | CTUh              | 1.28E-07 | 7.65E-10 | 3.37E-11 | 0  | 4.16E-11 | 3.24E-10 | 0  | 7.08E-09  |
| SQP       | SQP               | 2.31E+01 | 3.35E-03 | 8.21E-03 | 0  | 1.87E-04 | 2.99E-02 | 0  | -1.12E+00 |

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

This EPD was created using a software tool.

## References

### EN 1634-1

EN 1634-1:2018-04; Fire resistance and smoke control tests for door and shutter assemblies, openable windows and elements of building hardware - Part 1: Fire resistance test for door and shutter assemblies and openable windows

### UL 10C:3ED

UL 10C:3ED; 2016-06-09  
Positive Pressure Fire Tests of Door Assemblies

### EN 15804

EN 15804+A2:2019+AC:2021,  
Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

### EN 1634-1

EN 1634-1:2018-04, Fire resistance and smoke control tests for door and shutter assemblies, openable windows and elements of building hardware - Part 1: Fire resistance test for door and shutter assemblies and openable windows.

### ECHA

European Chemical Agency

### ISO 14025

DIN EN ISO 14025:201110, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

### REACH

Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

### RoHS

2011/65/EU, Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment

### UL 10c

Standard for Positive Pressure Fire Tests of Door Assemblies

### Further References

#### IBU 2021

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021. [www.ibu-epd.com](http://www.ibu-epd.com)

#### GaBi ts software

Sphera Solutions GmbH  
Gabi Software System and Database for Life Cycle Engineering  
19922020  
Version 10.0.0.71  
University of Stuttgart  
Leinfelden-Echterdingen

#### GaBi ts documentation

GaBi life cycle inventory data documentation  
(<https://www.gabisoftware.com/support/gabi/gabidatabase-2020-lcidocumentation/>).

#### LCA-tool dormakaba

Tool No.: IBU-DOR-202104-LT1-EN  
Developed by Sphera Solutions GmbH

#### PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Re-port according to EN 15804+A2:2019,  
Version 1.0, 2020, Institut Bauen und Umwelt e.V., [www.ibu-epd.com](http://www.ibu-epd.com).

#### PCR Part B

PCR – Part B: Requirements on the EPD for Building Hardware product, version 08/2021, Institut Bauen und Umwelt e.V., [www.ibu-epd.com](http://www.ibu-epd.com).





**Publisher**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
[info@ibu-epd.com](mailto:info@ibu-epd.com)  
[www.ibu-epd.com](http://www.ibu-epd.com)

---



**Programme holder**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
[info@ibu-epd.com](mailto:info@ibu-epd.com)  
[www.ibu-epd.com](http://www.ibu-epd.com)

---



**Author of the Life Cycle Assessment**

dormakaba International Holding GmbH  
DORMA Platz 1  
58256 Ennepetal  
Germany

+49 2333 793-0  
[info.de@dormakaba.com](mailto:info.de@dormakaba.com)  
[www.dormakaba.com](http://www.dormakaba.com)

---



**Owner of the Declaration**

dormakaba International Holding GmbH  
DORMA Platz 1  
58256 Ennepetal  
Germany

+49 2333 793-0  
[info.de@dormakaba.com](mailto:info.de@dormakaba.com)  
[www.dormakaba.com](http://www.dormakaba.com)