

SELECTO

PORCELAIN TILE



→ **POLISHED FINISH**

CREAM				
				
FORMATO NOMINAL / NOMINAL SIZE	60X120 CM RC 24"x48 RC	100X100 CM RC 40"x40" RC		
FORMATO FABRICACIÓN / WORK SIZE	59X119 CM RC 23,6"x46,9" RC	98X98 CM RC 38,6"x38,6"		
TIPO / TYPE	PORCELANICO ESMALTADO / GLAZED PORCELAIN TILE			
GRUPO / GROUP	Bla			
VARIACIÓN GRÁFICA / SHADE VARIATION	IV2			
DESCRIPCIÓN DEL TEST / TEST DESCRIPTION		NORMA / STANDARD	VALOR DEL TEST / TEST VALUE	EVALUACIÓN / EVALUATION
ABSORCIÓN DE AGUA / WATER ABSORPTION		UNE-EN-ISO 10545-3	Ev ≤ 0,5%	CUMPLE / COMPLIES
FUERZA DE ROTURA / BREAKING STRENGTH		UNE-EN-ISO-10545-4	≥ 1300 N	CUMPLE / COMPLIES
RESISTENCIA A LA FLEXIÓN / MODULUS OF RUPTURE		UNE-EN-ISO-10545-4	≥ 35 N/mm2	CUMPLE / COMPLIES
ABRASIÓN SUPERFICIAL / SURFACE ABRASION		UNE-EN-ISO -10545-7	VALOR DECLARADO / DECLARED VALUE	CREAM CLASE IV / CLASS IV
RESISTENCIA AL CUARTEO / CRAZING RESISTANCE		UNE-EN-ISO -10545-11	REQUERIDO / REQUESTED	CUMPLE / COMPLIES
RESISTENCIA AL LA HELADA / FROST RESISTANCE		UNE-EN-ISO -10545-12	REQUERIDO / REQUESTED	CUMPLE / COMPLIES
RESTISTENCIA A LAS MANCHAS / RESISTANCES TO STAINS		UNE-EN-ISO -10545-14	MÍNIMO CLASE 3 / MINIMUM CLASS 3	CUMPLE / COMPLIES
RESISTENCIA QUÍMICA / CHEMICAL RESISTANCE	PRODUCTOS DOMESTICOS Y DE PISCINA / HOUSEHOLD CHEMICALS AND SWIMMING POOLS SALTS	UNE-EN-ISO -10545-13	MINIMO CLASE B / MINIMUM CLASS B	CUMPLE / COMPLIES
	ÁCIDOS A BAJA CONCENTRACIÓN / LOW CONCENTRATION ACIDS	UNE-EN-ISO -10545-13	VALOR DECLARADO / DECLARED VALUE	MÍNIMO CLASE LB / MINIMUM CLASS LB
	BASES A BAJA CONCETRACIÓN / LOW CONCENTRATION OF ALKALIS	UNE-EN-ISO -10545-13	VALOR DECLARADO / DECLARED VALUE	MÍNIMO CLASE LB / MINIMUM CLASS LB
RESISTENCIA AL RAYADO / HARDNESS (MOHS)		EN-101	VALOR DECLARADO / DECLARED VALUE	MÍNIMO 3 / MINIMUM 3