







STIXX &

AUTOMATIC FIRE SUPPRESSION UNIT

www.maussafety.com



EN





KEY FEATURES



FLOODING

Once activated it will release 100% of it's content.



NON TOXIC

The potassium formula is 100% non toxic & environmentally friendly.



FAST

Activation at very low temperature - 180 °C.



MAINTENANCE

Maintenance free during its 5 year life span.



SIZE

With its small size you can place the unit anywhere.




SYSTEM


No complex system. No wiring. No batteries. No pressure.


LAYERS





DISTRIBUTION BOARD INSTALLATION





















PRO > ROW > ROW > PRO

In larger distribution boards, if the fire starts at a lower point, there could be multiple cables and fuses that prevents the hot smoke and fire to reach the Stixx PRO in order for it to activate fast. To make sure that the Stixx PRO will activate fast we need to add another Stixx PRO according to the rule "pro - row - row - pro". Of course if there are only two rows you don't need an extra Stixx PRO. See EXAMPLE 2 below (Examples).

The Easy Rule:

PRO > ROW > ROW > PRO





Distribution Boards

EXAMPLE 1



FXAMPLE 3




4




EXAMPLE 2


EXAMPLE DISTRIBUTION BOARD



Normal distribution board with 4 rows.



With so many cables you can not place it on the back wall or in the ceiling.



The best option is to place them on the inside of the panel door. *Pro, row, row, pro!*



VOLUME CABINETS CALCULATE THE VOLUME

The difference between distribution boards and volume cabinets.

HOW TO CALCULATE THE VOLUME:

HEIGHT (H) X WIDTH (W) X DEPTH (D)



A **VOLUME CABINET** is a cabinet that has free space inside, It does not have rows with fuses like a distribution board so we need to calculate the volume instead.

EXAMPLES LESS THAN 1M TALL


VOLUME: 0.1m³ VOLUME: 0.2m³ STIXX PRO: 1 STIXX PRO: 2
Place the units in the ceiling of the cabinet.


- IF THE HEIGT IS MORE THAN 1M
 AND VOLUME LESS THAN 0.1 M³:
 Place 1x Stixx PRO in the ceiling,
 and 1x Stixx PRO in the middle.
- IF THE HEIGHT IS MORE THAN 1M AND VOLUME 0.1-0.2m³:
 Place 2x Stixx PRO in the ceiling.
 and 2x Stixx PRO in the middle.

IMPORTANT! If the space is ventilated you need to double (x2) the amount of Stixx PRO's.



Caravan







VOLUME CABINET! If the space is 0 to $0.1 \text{m}^3 = 1 \text{ x Stixx PRO. } 0.1 \text{ to } 0.2 \text{m}^3 = 2 \text{ x Stixx}$ PRO. 0.2 to 0.3m³ = 3 x Stixx PRO etc. Place the Stixx PRO's close to each other







EXAMPLES

Motorboat



1. REMOVE THE TOP Always remove the top and install the device when the motor is cool.



3. AUTOMATIC ACTIVATION At 180°C the unit will activate underneath the top and supress the fire.



MORE MAUS TECHNOLOGY



PGA FIRE EXTINGUISHER -MAUS XTIN KLEIN

Innovative fire extinguisher that extinguishes all kinds of smaller fires in the initial phase with potassium based aerosol (smoke). Non pressurised. Residue free technology. 5 year warranty. Comes with a light plastic wall mount.

Art no: 1001-1 Length: 242 mm. Width: Ø50 mm. Weight: 480 g. Fire Classes: 8BC

Certified by RINA S.p.A, BAM & CE. 8BC.
Best Innovation Award 2021 at Secours Expo.



HOLSTER -HOLSTER KLEIN

Attach the holster on your belt by opening the loop in the rear of the holster or use the metal ring to attach it to your toolbelt / safety guard belt. Perfect for police, safety guards, electricians etc.

Art no: 1101-1 Length: 250 mm. Width: Ø55. Weight: 75 g.



PGA FIRE EXTINGUISHER MAUS XTIN GRAND

Same innovation as MAUS Xtin Klein, but 3 times more powerful, Perfect for larger vehicles, boats and production facilities, Residue free technology, 5 year warranty. Comes with a quality metal wall mount.

Art no: 3001-1 Length: 236 mm. Width: Ø120 mm. Weight: 1750 g. Fire Classes: 21 BC Certified by RINA S.p.A & CE. 21BC.



NOZZLE EXTENSION -NOZZLE KLEIN

Extend the MAUS Xtin Klein with NOZZLE Klein and insert it in your boats Fire Port, underneath the bonet of your car or in any situation where you don't want to open a cabinet/door more than necessary to fight the fire.

Art no: 1201-1 Length: 240 mm. Width: Ø55 mm. Weight: 108 g.



FIRE BLANKET -MAUS DEKKE HOME

The stylish hard, gloss finish, white plastic cover will be a nice safety feature in your home, caravan, boat or office. 1.2 x 1.8m. Unique feature with pockets to protect the hands.

Art no: 5001-1 Length: 368 mm. Width: 176 mm. Depth: 60 mm. Weight: 1300 g.

Certified according to SS-EN-1869:1997



FIRE BLANKET MAUS DEKKE MOBIL

Same fire blanket as MAUS Dekke Home, but with a soft cover. Perfect for glove compartments in the car, boats, caravans and home. 1.2 x 1.8 meters and certified. Unique feature with pockets to protect the hands.

Art no: 5002-1 Length: 330 mm. Width: 185 mm. Depth: 40 mm. Weight: 1096 g. Certified according to SSEN3:1997



WALL MOUNT -HALTER KLEIN

HALTER Klein is a smart protective cover (wall bracket) for MAUS Xtin Klein. The protective cover protects against dust and water splashes. It fits nicely into all types of private and public environments. You easily pull the tab to remove the cover.

Art no: 1401-1 Length: 282 mm. Width: 77 mm. Height: 67 mm. Weight: 140 g.



SMOKE ALARM -MAUS RAUCH Wifi

MAUS Rauch Wifi is the smart photoelectric / optical smoke alarm that is able to detect any fire in your house, boat, camper van, summer cottage or office and send notifications to your Smartbhone.

Art no: 6001-1 Dimensions: Ø132 x Width 42 mm Including batteries. CE certified



FIRE SUPPRESSION -MAUS STIXX PRO 5

MAUS Stixx PRO 5 is an automatic fire suppression device that is five times more powerful than MAUS Stixx PRO. It comes with a smart detection cable that can be extended from the unit in order to detect heat faster. Designed for larger electric enclosures and spaces.

Art no: 1360-1 Dimensions: 15 x 60 x 60 mm Protected space: 0.5 m³ CF Certified (CF 2829)

SPECIFICATIONS MAUS STIXX PRO

Discharge time: ≤5s Type: Automatic Fire Suppression Unit Protected area: Article number: 1350-1 $0.1 \, \text{m}^3$ EAN: 7350015530157 Activation Temperature: 180°C±10°C Operational Temperature: -30°C - 70°C Dimensions: 9.8 x 1.8 x 1 cm Weight: Certifications: CE 2829 26q Product life: 5 years (6 year shelf life) Awards in Sweden: Best Electric Innovation 2021